

ATION
USA
FILM
INHIBITOR-PATENT
INHIBITOR



HIGH PERFORMANCE VpCI® PACKAGING

Desicorr® Pouches/NW



PRODUCT DESCRIPTION

Desicorr® is a specially designed pouch to protect products from moisture damage. Whether in storage or in transit, products in nearly every industry require protection from moisture.

Mildew, mold, rust, and an overall decrease in product efficacy are all common effects of moisture, costing millions in returned or unusable products each year. Desicorr® pouches help prevent damage by absorbing moisture.

Desicorr® Pouches are available in both windowed and non-windowed versions (NW). The windowed version contains some indicator spheres that will change color from yellow to green when the desiccant is fully spent.

FEATURES

- Available in 1/6, 1, and 2 Unit sizes
- No degreasing or cleaning of protected part required
- Commercially equivalent to MIL-D-3464E, Type I & Type II
- Can be easily inserted into package manually or automatically

TYPICAL APPLICATION

Desicorr® Pouches are designed to protect goods within a sealed moisture barrier package or container from moisture damage. Successful usages include:

- Semiconductors
- Electronics components
- Circuit boards
- Relays, communication devices
- Museum storage
- Optical devices
- Military instruments
- Machine parts

METHOD OF APPLICATION

Manually or automatically insert a Desicorr® pouch into the package. The number may vary depending on shipping conditions and the nature of the products being protected.

Unit Size	Pouch Dimensions	Moisture Absorption Capacity (g) at 77°F, 75% R.H.
1/6	2.75" x 2.5" x 0.25" (7 cm x 6.4 cm x 0.6 cm)	1.6
1	7" x 4" x 0.5" (17.8 cm x 10.2 cm x 1.2 cm)	11.55
2	7" x 4" x 0.5" (17.8 cm x 10.2 cm x 1.2 cm)	23.1


STANDARD TEST REFERENCE CHART

MIL-D-3464E	Activated, Bagged Desiccant
-------------	-----------------------------

PACKAGING AND STORAGE

Desicorr® Pouches come in cartons of 300 units. Store the product at room temperature. Close cartons between uses. The shelf life of unopened cartons of Desicorr® Pouches is up to 24 months. Desiccant spheres can be reused if heated to release moisture.

Water Absorption Capacity Of Desicorr®



FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN
KEEP CONTAINER TIGHTLY CLOSED
NOT FOR INTERNAL CONSUMPTION
CONSULT SAFETY DATA SHEET FOR MORE INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec® Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec® Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec® Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec® Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec® Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.
 BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE,

AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec® Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC® CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



4119 White Bear Parkway, St. Paul, MN 55110 USA
 Phone (651) 429-1100, Fax (651) 429-1122
 Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
<http://www.cortecvci.com>

Printed on recycled paper  100% post consumer

Revised: 11/26/18. Supersedes: 04/19/17. ©Cortec Corporation 2002-2018 of Cortec Corporation. All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited. 2018, ©Cortec Corp. ISO accreditation applies to Cortec's processes only.

Distributed by:



Valdamark Limited
 Unit 13,
 30 The Downs
 Altrincham, Cheshire, WP14 2PX,
 United Kingdom.
valdamark@live.com
 Tel: +44 (0) 161 706 0388

