



# ElectriCorr® VpCI®-248



## PRODUCT DESCRIPTION

Designed for use in a sheltered environment, ElectriCorr VpCI-248's continuous vapor action saves money by extending product life and eliminating downtime due to corrosion. ElectriCorr VpCI-248 forms a molecular film effective against aggressive environments including industrial, marine, and tropical climates. This film does not alter the electrical, resistance, or magnetic properties. ElectriCorr VpCI-248 can be safely applied for protection of even low-voltage circuits or relays without causing any changes in conductivity. In addition to corrosion protection, ElectriCorr VpCI-248 is an excellent contact cleaner of oils, grime, and other contaminants.

ElectriCorr VpCI-248 is an effective inhibitor of galvanic corrosion for most metals and alloys normally found in electronic applications such as aluminum, copper, ferrous, and non-ferrous metals. Application provides instant corrosion protection. ElectriCorr VpCI-248 is thermally stable, non-flammable, and based on environmentally sensible fluorocarbon solvents, which are exempt from VOC regulations by the US EPA.

## FEATURES

- Non-flammable
- Instant corrosion protection
- Long-term protection
- Minimized field service
- Increased corrosion protection at a lower cost than conventional rust preventives
- CFC and 1,1,1-Trichlorethane-free
- Not listed as ODP, MAP, or SARA reportable
- The carrier solvents are exempt from VOC regulations by the US EPA (October 8, 1996, September 24, 1997, Federal register)
- Vapor phase protection in vented or unvented enclosures
- May be used as a cleaning and defluxing agent
- Moisture-displacing and penetrating film characteristics

## TYPICAL APPLICATIONS

- Ideal for general and precision cleaning
- Printed circuit boards
- Electrical contacts and components
- Electric motors
- Protects copper bearings, ferrous and non-ferrous metals, aluminum, etc.
- Can be used in contact with majority of engineering plastics, elastomers, and other non-metallics
- Generators and junction boxes
- Spray for use after final assembly or in the field



## APPLICATION

Spray a very light mist over the area needing protection. Application is effective for 6+ months with proper controls.

**Note:** Application of a heavy mist will result in a heavy film that sags and remains wet. More is not necessarily better and could cause fouling or other complications of electrical connections.

**Note:** Compatibility on plastics, elastomers, and painted surfaces should be verified prior to any potential interaction.

## PHYSICAL PROPERTIES OF LIQUID

Appearance	Clear slightly yellow liquid
Density	10.1-10.5 lb/gal (1.21-1.26 kg/l)

## PACKAGING AND STORAGE

ElectriCorr VpCI-248 aerosol spray is available in cartons of six 12 oz. (340 gram) cans. ElectriCorr VpCI-248 should be kept from high temperatures and in normal warehouse conditions to prevent from freezing. ElectriCorr VpCI-248 has a shelf-life of 3+ years in sealed packages.

## FOR INDUSTRIAL USE ONLY

**KEEP OUT OF REACH OF CHILDREN**

**KEEP CONTAINER TIGHTLY CLOSED**

**NOT FOR INTERNAL CONSUMPTION**

**CONSULT SAFETY DATA SHEET FOR MORE INFORMATION**

## LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.


**BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.** No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

**THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.**



Environmentally Safe VpCI®/MCI® Technologies

4119 White Bear Parkway, St. Paul, MN 55110 USA  
Phone (651) 429-1100, Fax (651) 429-1122  
Toll Free (800) 4-CORTEC, E-mail [info@cortecvci.com](mailto:info@cortecvci.com)  
Internet <http://www.cortecvci.com>

printed on recycled paper  100% post consumer  
Revised: 1/5/16. Cortec Corporation 2002-2016. All rights reserved. Supersedes: 6/30/11.  
ElectriCorr® and VpCI® are trademarks of Cortec Corporation.  
© 2016, Cortec Corporation. All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited. ISO accreditation applies to Cortec's processes only.

Distributed by:



**Valdamark Limited**  
Unit 13,  
30 The Downs  
Altrincham, Cheshire, WP14 2PX,  
United Kingdom.  
[valdamark@live.com](mailto:valdamark@live.com)  
Tel: +44 (0) 161 706 0388

