

VpCI®-426 Gel



PRODUCT DESCRIPTION

VpCI-426 Gel removes corrosion, scale, and naturally occurring oxides from iron, carbon and stainless steel, and their alloys.

VpCI-426 Gel stays in place on vertical and difficult to treat surfaces where corrosion is heavy, allowing extra time for VpCI-426 Gel to remove corrosion from the metal surface.

TYPICAL USES

- Removes corrosion from ferrous metals and copper
- Oxide removal of brass, bronze, copper, and zinc

ADVANTAGES

- Very effective on carbon steel and stainless steel to dissolve rust, scale, and oxide deposits
- Reduced toxicity and costs
- Increased performance over equivalent products
- Can be used in areas that can not be sandblasted or cleaned with power tools
- Non-toxic and nitrite free

APPLICATION

Use* on mil scale, overnight cleaning, and vertical/overhanging areas. Once corrosion has been removed it is advised to use Cortec® VpCI-414 (1:5 and 1:10 dilutions) to rinse away any residue and to prevent the metal surface from flash rusting.

*Time to remove problem areas will vary with temperatures and substrate.

PHYSICAL PROPERTIES

Appearance	Clear gel
Density	8.7-9.0 lb/gal (1.04-1.08 kg/l)
Non-volatile Content	25-30%

PACKAGING

VpCI-426 Gel is available in 5 gallon (19 liter) pails and 55 gallon (208 liter) drums. The minimum storage temperature is 32°F (0°C). The maximum storage temperature is 100°F (38°C).

FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN
KEEP CONTAINER TIGHTLY CLOSED
NOT FOR INTERNAL CONSUMPTION
CONSULT SAFETY DATA SHEET FOR MORE
INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
Internet <http://www.cortecvci.com>

printed on recycled paper  100% post consumer
Revised: 9/27/13. ©Cortec Corporation 2000-2013. Supersedes: 2/14/13.

Cortec® is a trademark of Cortec Corporation. © 2000-2013, ©Cortec Corporation. All Rights Reserved. 2013, ©Cortec Corporation. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited. ISO accreditation applies to Cortec's processes only.

Distributed by:



Valdamark Limited
Unit 13,
30 The Downs
Altrincham, Cheshire, WP14 2PX,
United Kingdom.
valdamark@live.com
Tel: +44 (0) 161 706 0388

