

VpCI®-649 BD/VpCI®-649 BD MF

DESCRIPTION

VpCI®-649 BD is a unique concentrated liquid formulation designed to provide long-term protection for ferrous and non-ferrous metals in water and glycol closed-loop systems. VpCI®-649 BD is effective at corrosion protection during hydrostatic testing.

VpCI®-649 BD combines contact and volatile corrosion inhibitors, along with anti-scalant and an organic dispersing agent. The product does not contain nitrite, phosphate, or chromate.

VpCI®-649 BD is available in a molybdate-free version: VpCI®-649 BD MF.

PACKAGING & STORAGE

VpCI®-649 BD is available in 5 gallon (19 liter) pails, 55 gallon (208 liter) drums, liquid totes, and bulk.

To ensure best product performance, store in original packaging, indoors, and out of direct sunlight at 40-100 °F (4-38 °C).

Shelf life: 2 years

VpCI® ADDITIVES FOR WATER TREATMENT



FEATURES

- Effective for a broad range of applications to stop aggressive corrosion in systems containing fresh water or glycol coolants
- Low concentration effectiveness provides economical treatment
- Vapor phase action provides protection to areas that contact inhibitor cannot reach
- Protects steel, copper, galvanized steel, and aluminum
- Contains an acrylic polymer to prevent scale formation
- VpCI®-649 BD contains molybdate tracer
- VpCI®-649 BD MF contains a PTSA tracer
- Contains organic dispersing agent

TYPICAL PROPERTIES

Appearance	Yellow to Amber Liquid
Density	9.3-9.8 lb/gal (1.12-1.18 kg/L)
Type	Water-Based
pH	9.1-9.6 (Neat)
Freeze Point	1 to 10 °F (-17 to -12 °C)

APPLICATIONS

- Closed loop cooling systems
- Hydrostatic testing of pressurized vessels and pipelines
- Cooling system lay-up
- Packer fluid additive
- Prevents water-bottom corrosion in oil storage tanks
- Fire extinguishing system dry layup

VpCI®-649 BD/VpCI®-649 BD MF

DOSAGE

Protection Length	Volume VpCI®-649 BD per 100 gal	Volume VpCI®-649 BD per 100 L	Dosage (%)	ppm
During Testing & Operational Protection	0.3 gallons (38 ounces)	300 mL	0.3	3000
Up to 6 months	0.5 gallons (64 ounces)	500 mL	0.5	5000
6-12 months	1 gallon	1 L	1	10,000
12-24 months	1.5 gallons	1.5 L	1.5	15,000

**These are general dosing guidelines and may not be suitable for every application. Please contact Cortec® Technical Service for specific dosage information.*

Detection: Concentration of VpCI®-649 BD can be monitored via molybdate tracer, pH, or refractometer. Concentration of VpCI®-649 BD MF can be monitored via pH, refractometry, or PTSA. Contact Cortec® Technical Service for more information on monitoring product concentration.

STANDARD TEST METHODS

Method	Description	Results
ASTM G 31	Immersion Corrosion Testing	No corrosion on carbon steel, copper galvanized, aluminum (0.3% wt in tap water)

CONSIDERATIONS

The PTSA tracer used in VpCI®-649 BD MF degrades with exposure to light. Solutions of VpCI®-649 BD MF must be sheltered from light to retain PTSA tracer. If PTSA degrades, the concentration can still be monitored via a titration. Contact Cortec® Technical Service for more information.

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec® Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec® Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec® Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec® Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec® Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec® Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC® CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC
info@cortecvci.com
https://www.cortecvci.com
https://www.cortecwatertreatment.com

Distributed by:



Valdamark Limited
Unit 13,
30 The Downs
Altrincham, Cheshire, WP14 2PX,
United Kingdom.
valdamark@live.com
Tel: +44 (0) 161 706 0388



Revised: 02/18/2022 . Supersedes: 08/27/2019. ©Cortec Corporation 2002-2020 of Cortec® Corporation. All Rights Reserved. Copying and/or manipulation of these materials in any form without the written authorization of Cortec® Corporation is strictly prohibited. 2020, ©Cortec® Corp. ISO accreditation applies to Cortec's processes only.

