

ATION
USA
FILM
INHIBITOR-PATENT
INHIBITOR



HIGH PERFORMANCE VpCI® PACKAGING

EcoWeave® VpCI® Woven Polypropylene



Woven polypropylene is a durable, but lightweight material for all your demanding projects. It utilizes a high density polypropylene scrim as its base material and is then coated with a layer containing volatile corrosion inhibitors to provide the proven corrosion protection of Cortec® VpCI® film technology.

CORROSION PROTECTION

Metal parts packaged in EcoWeave® receive continuous protection against excessive humidity, condensation, moisture, and aggressive industrial atmospheres. The VpCIs vaporize and then condense on all metal surfaces in an enclosed package. EcoWeave® offers complete product protection during storage, as well as domestic and overseas shipments, virtually eliminating any rust claims. EcoWeave® can be custom manufactured in heavier weights to suit all shipping or storage requirements.

DESCRIPTION

EcoWeave® is a woven polypropylene sheeting that offers extra strength, durability, corrosion protection, reusability, and recyclability. EcoWeave® is the new solution for tough corrosion packaging problems. From raw materials to finished product, EcoWeave® will provide the protection you need for expensive, but heavy, raw materials and finished products. It provides protection against corrosion, mother nature, traditional transit, and storage damage.

Use EcoWeave® for:

- Export packaging of expensive and larger equipment
- Steel sheeting and flat stock
- Steel coils
- Pallet shrouds
- Heavy equipment covers
- Heavy metal parts
- Equipment and product pouches
- It can be custom sewn for an exact fit

ADVANTAGES

EcoWeave® offers strength, tear resistance, durability, and protection from corrosion. Many packaging applications require a tear resistant shroud to accommodate the sharp edges of equipment or steel coil during shipment. The woven structure of EcoWeave® will help prevent damage to the shroud, thus preserving the integrity of the VpCI® protection and preventing corrosion from occurring.

PHYSICAL PROPERTIES

Property	Test Method	Units	Value [Warp/Weft]
Unit Weight		oz/yd ² (g/m ²)	3.3 (33.9)
Elongation	ASTM D5034-09		15.3% / 15.4%
Tensile Strength	ASTM D5034-09	lb _f (N)	80.1 (356.3) / 79.6 (354.0)
Tearing Strength	ASTM D4533-15	lb _f (N)	25.5 (113.4) / 26.4 (117.3)
Burst Strength	ASTM D3787-16	lb _f (N)	79.4 (353.3)
Width		in (cm)	Up to 144 (366)

METALS PROTECTED

- Carbon Steel
- Stainless Steel
- Aluminum
- Cast Iron

PACKAGING AND STORAGE

Available in standard and custom sizes. Contact Cortec® Customer Service for inquiries and custom requirements.

**FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN
KEEP CONTAINER TIGHTLY CLOSED
NOT FOR INTERNAL CONSUMPTION
CONSULT SAFETY DATA SHEET FOR MORE
INFORMATION**

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec® Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec® Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec® Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec® Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec® Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.
BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE,

AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec® Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC® CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
<http://www.cortecvci.com>

Printed on recycled paper  100% post consumer

Revised: 09/21/17. Supersedes: 05/09/14. ©Cortec Corporation 2002-2017 of Cortec Corporation.
All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited. 2017, ©Cortec Corp. ISO accreditation applies to Cortec's processes only.

Distributed by:



Valdamark Limited
Unit 13,
30 The Downs
Altrincham, Cheshire, WP14 2PX,
United Kingdom.
valdamark@live.com
Tel: +44 (0) 161 706 0388

