



CORTEC
CORPORATION

Environmentally Safe VpCI®/MCI® Technologies

VpCI®-126 Vacuum Bags

DESCRIPTION

VpCI®-126 Vacuum Bags are transparent Vapor phase Corrosion Inhibitor bags with extra barrier properties for enhanced corrosion protection during long-term storage or harsh shipping conditions. The bags can be vacuum-packed and are ideal for build-ahead programs and all-time-buys. Metal parts packaged in VpCI®-126 Vacuum Bags receive continuous protection against salt, excessive humidity, condensation, moisture, aggressive industrial atmospheres, and dissimilar metal corrosion. The VpCI® molecules vaporize and then condense on metal surfaces in the enclosed package, forming a protective molecular film that does not need to be cleaned off, so contents can be used immediately.

PACKAGING & STORAGE

VpCI®-126 Vacuum Bags are available in a variety of custom sizes.

To ensure best product performance, store in original packaging, indoors, and out of direct sunlight at 40-100 °F (4-38 °C).

Shelf life: 2 years

HIGH PERFORMANCE VPCI® PACKAGING



FEATURES

- Extra barrier for moisture and oxygen
- Can be used on vacuum-packaging equipment
- Does not contain free amines, phosphates, or halogen-based materials
- Commercial equivalent to MIL-PRF-22019E(1)
- NACE TM0208-2008
- Meets German TL-8135-002 standard for corrosion protection

BENEFITS

- Enhanced corrosion protection for long-term storage
- Easy to inspect contents through transparent film
- Great for unitizing loads and eliminating rubbing of small parts during transit and storage
- Replaces conventional rust preventatives such as oils and desiccants

APPLICATION

Place metal parts inside bags and seal using standard vacuum-packaging equipment.

METALS PROTECTED

- Aluminum
- Galvanized Steel
- Carbon Steel
- Stainless Steel
- Copper
- Brass
- Cast Iron

VpCI®-126 Vacuum Bags

TYPICAL PROPERTIES

Property		Test Method	Units	VpCI®-126 Vacuum Bags
Caliper		ASTM D6988	mil	4.95
Breaking Factor	MD	ASTM D882-02	lbs/in	21.94
	CD			19.14
Tensile Strength at Break	MD	ASTM D882-02	psi	4875.00
	CD			4373.00
Elongation at Break	MD	ASTM D882-02	%	102.82
	CD			116.59
Yield Strength	MD	ASTM D882-02	psi	4240.48
	CD			4200.73
Tear Strength	MD	ASTM D1922-06A	mN	307.20
	CD			294.40
Dart Drop Impact Resistance		ASTM D1709-04, Test Method A	grams	603.70
Puncture Resistance	Outside	MIL-STD-3010, TM 2065	lbf	10.87
	Inside			10.75
Coefficient of Friction		ASTM D1894	static	0.00
			kinetic	0.51
Water Vapor Transfer Rate (100.4 °F [38 °C], 90% RH)		ASTM F1249	g/100 in ² /24 hours	0.0043
			g/m ² /24 hours	0.067
Oxygen Transfer Rate (73 °F [23 °C], 0% RH)		ASTM D3985	cc/100 in ² /24 hours	0.003
			cc/m ² /24 hours	0.046



LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec® Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec® Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec® Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec® Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec® Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec® Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC® CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



4119 White Bear Parkway, St. Paul, MN 55110 USA
 Phone (651) 429-1100, Fax (651) 429-1122
 Toll Free (800) 4-CORTEC
 info@cortecvci.com
<https://www.cortecvci.com>
<https://www.cortecpackaging.com>

Distributed by



Valdamark Limited
 Unit 13,
 30 The Downs
 Altrincham, Cheshire, W14 2PX,
 United Kingdom.
 valdamark@live.com
 Tel: +44 (0) 161 706 0388

