


ATION  
USA  
FILM  
INHIBITOR-PATENT  
INHIBITOR



**HIGH PERFORMANCE VpCI® PACKAGING**

**VpCI®-130 Series  
Impregnated Foams Patented  
Multifunctional VpCI®, Desiccant and Antistatic Action**



**BENEFITS**

VpCI®-130 Series Foams are nitrite- and chromate-free. The high performance patented formulation of VpCI® provides fast, easy-to-use protection even in aggressive overseas shipments.

VpCI®-130 Series Foams contain approximately ten (10) times more VpCI® chemical per square foot (square meter) of substrate than the traditional VCI papers and other wrapping materials. This makes the protection of objects with large surface areas possible (i.e.: aluminum and steel coils). The unique combination of high and low vapor pressure VpCIs contained in VpCI®-130 Series Foams affords long-term protection for large export packages, crates, and seagoing containers.

Combine VpCI®-130 Foam with Cortec® VpCI®-125/126 film to create a highly effective VpCI® packaging solution.

**PRODUCT DESCRIPTION**

Cortec® VpCI®-130 Series Foams are unique flexible packaging materials that combine VpCI® protection, and desiccant action; plus excellent antistatic capabilities all in one step! You can now eliminate expensive and messy rust preventatives with VpCI®-130 Series Foams. Parts protected are always ready for use; no degreasing or coating removal is required. Application of multifunctional materials such as VpCI®-130 Series Foams results in significant weight and labor savings.

Metal parts packaged with VpCI®-130 Series Foams receive continuous protection against humidity, condensation, aggressive industrial atmospheres, dissimilar metal corrosion (galvanic corrosion), salt air, and residual impurities left after processing.

National Stock Number:  
#3850-01-426-3539

**FEATURES**

Cortec® VpCI®-130 Series Foams are specially designed with Vapor phase Corrosion Inhibitor (VpCI®) impregnated throughout the foam's polymeric matrix. They are excellent for protection of ferrous, non-ferrous metals, and alloys such as: steel, copper, brass, aluminum, zinc, solder, silver, etc. VpCI®-130 Series Foams do not change critical physical and/or chemical properties of electronic components, and are suitable for protection of printed circuit boards.

**TYPICAL APPLICATION**

VpCI®-130 Series Foam forms a strong protection as long as the enclosure remains sealed and there are no barriers between the metal surface and the VpCI® molecules. The placement of the foam is not important as long as it has access to the same air space as the metal to be protected. This product line is not intended to be used for cushioning purposes; excess pressure applied to the foam can wring the inhibitor from the substrate. In some situations this may leave a residue on the surface which will need to be removed with water or rubbing alcohol.

Product	Sizes in Inches (Centimeters)	Protection Volume
131	2 x 10 (5.08 x 25)	1.5 ft³ (.042 m³)
132	10x10 (25x25)	8 ft³ (0.23 m³)
133	1x1 (2.5x2.5) (adhesive back)	0.25 ft³ (7L)
136	1x 1 (2.5 x 2.5)	0.25 ft³ (7L)
137	130' x 4.5' (39.6m x 1.35m)	10ft³/ft² (3m³/m²)



## METALS PROTECTED (MULTI-METAL)

- Aluminum
- Galvanized Steel
- Brass
- Solder
- Carbon Steels
- Silver
- Copper
- Zinc

## STORAGE AND PACKAGING

VpCI®-130 Series Foam has a shelf life of 2 years when sealed in the original package. To maintain VpCI® strength, unused foam should be kept sealed in plastic bags.

## STANDARD TEST METHODS

NACE TM 0208-2008	Vapor Inhibiting Ability
NACE RP 0487-2000	Selection of Rust Preventative
MIL-PRF-26514G, Type 3, Class II	Polyurethane Foam

**FOR INDUSTRIAL USE ONLY**  
**KEEP OUT OF REACH OF CHILDREN**  
**KEEP CONTAINER TIGHTLY CLOSED**  
**NOT FOR INTERNAL CONSUMPTION**

### LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec® Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec® Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec® Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec® Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec® Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.  
BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE,

AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec® Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC® CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



4119 White Bear Parkway, St. Paul, MN 55110 USA  
Phone (651) 429-1100, Fax (651) 429-1122  
Toll Free (800) 4-CORTEC, E-mail [info@cortecvci.com](mailto:info@cortecvci.com)  
<http://www.cortecvci.com>

Printed on recycled paper  100% post consumer

Revised: 09/16/16. Supersedes: 06/20/16 ©Cortec Corporation 2002-2016 of Cortec Corporation.  
All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited. 2016, ©Cortec Corp. ISO accreditation applies to Cortec's processes only.

Distributed



**Valdamark Limited**  
Unit 13,  
30 The Downs  
Altrincham, Cheshire, WP14 2PX,  
United Kingdom.  
[valdamark@live.com](mailto:valdamark@live.com)  
Tel: +44 (0) 161 706 0388

