



# VpCI®-337 F



## PRODUCT DESCRIPTION

VpCI-337 F is a ready-to-use, FDA compliant, USDA approved, solvent-based corrosion inhibitor for indoor use. Vapor phase inhibitors in VpCI-337 F migrate and protect metal surfaces, resulting in time and cost savings. With VpCI-337 F, very little product is needed to protect large areas or volumes. It is effective on ferrous metals as well as aluminum and plated steels.

Products protected by VpCI-337 F are always ready-to-use; no degreasing or stripping is necessary. The metal will retain a clean, rust-free surface. The thin, protective film has been proven not to affect paintability, conductivity, appearance, or any other important property of metals or alloys.

VpCI-337 F is FDA compliant (21CFR 178.3300) for use in packaging materials for the packaging of steel, tinfoil, or articles fabricated therefrom; including food containers, food-processing or handling equipment.

VpCI-337 F's ingredients are further approved by the United States Department of Agriculture for use on packaging material for indirect contact with meat and poultry food products.

## TYPICAL APPLICATIONS

- In-process protection
- Edge spray of coils and sheet stock
- Void spaces
- Double wall void spaces

## FEATURES

- Contains vapor phase inhibitors which provide multimetal corrosion protection
- Leaves a thin, self-healing film that is environmentally approved for use
- Ready-to-use
- Protection is immediate, convenient to apply, and easy to remove if required
- Gives up to 12 months indoor protection
- Contains FDA compliant and USDA approved ingredients for use on tinfoil, aluminum, and other metal products used in food processing or packaging

## METALS PROTECTED

- Hot-/cold-rolled steel
- Cast iron
- Silicon steel
- Stainless steel
- Zinc
- Aluminum
- Tinfoil

## PHYSICAL PROPERTIES

Appearance	Clear to hazy, amber to brown liquid
Carrier	Ethanol
Film type	Thin, soft film
Flash Point	80°F (27°C)
Non-volatile Content	12-17%
pH	7.5-8.5 (Neat)
Density	7.6-7.8 lb/gal. (0.91-0.93 kg/l)



## APPLICATION

Coils, stack, and sheets are readily protected with easy-to-apply, effective, and long-lasting VpCI-337 F. Spray a fine mist of VpCI-337 F uniformly on laps and edges. The unique vapor action will protect the interior surfaces that are subject to attack by moisture. VpCI-337 F does not interfere with sensitive painting, lithographing, or welding processes. All grades of cold and hot-rolled steel, aluminum, black and tinplate, silicone, electrical, aluminized, and precoated steels can be treated with VpCI-337 F. VpCI-337 F can also be applied in-process for corrosion protection between pickling and annealing, after temper rolling, and after quenching, drawing, stamping, slitting, hydrotesting, and other processes.

Fog or mist VpCI-337 F concentrate into containers, boxes, crates, and shrouded packages at a rate of 1 pint (0.4 liter) for every 50 ft<sup>3</sup> (1.4 m<sup>3</sup>) of enclosed space. Spray on cardboard, wood pallets, closed and open cell foams, metal container, and other packaging materials. Always spray VpCI-337 F uniformly within enclosures and allow direct access of vapors to metal surfaces to be protected.

## PACKAGING AND STORAGE

VpCI-337 F is available in 5 gallon (19 liter) plastic pails, 55 gallon (208 liter) metal drums, liquid totes, and bulk. Shelf life is 24 months.

Minimum storage temperature: 32°F(0°C)  
Maximum storage temperature: 120°F (49°C)

## FOR INDUSTRIAL USE ONLY

### KEEP OUT OF REACH OF CHILDREN

### NOT FOR INTERNAL CONSUMPTION

### CONSULT SAFETY DATA SHEET FOR MORE INFORMATION

## LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



4119 White Bear Parkway, St. Paul, MN 55110 USA  
Phone (651) 429-1100, Fax (651) 429-1122  
Toll Free (800) 4-CORTEC, E-mail [info@cortecvci.com](mailto:info@cortecvci.com)  
Internet <http://www.cortecvci.com>

printed on recycled paper  100% post consumer  
Revised: 1/5/16. ©Cortec Corporation 1999-2016. All rights reserved. Supersedes: 8/2/13.

© 2016, Cortec Corporation. All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited. ISO accreditation applies to Cortec's processes only.

Distributed by:



**Valdamark Limited**  
Unit 13,  
30 The Downs  
Altrincham, Cheshire, WP14 2PX,  
United Kingdom.  
[valdamark@live.com](mailto:valdamark@live.com)  
Tel: +44 (0) 161 706 0388

