

TRAILER-MOUNTED MESSAGE SIGN

Ver-Mac's PCMS-548 is a mini full-matrix trailer-mounted portable changeable message sign. It displays 3 lines and 9 characters (8.75 in.) per line by default, with the ability of displaying multiple fonts, lines of text and graphics. This unit comes equipped with our Stealth Technology, NTCIP-compliant* V-Touch Controller, V-Sync Wi-Fi communication and JamLogic® Fleet Management Software.

Cutting-edge technology an energy-efficient design, and high-quality construction are combined to provide the most reliable, cost-effective and safe to operate message sign on the market. The PCMS-548 is perfect for lower speed roadways and urban areas.

PRO SERIES FEATURES

STEALTH TECHNOLOGY

Sealed maintenance-free batteries Anti-theft hidden battery compartment

V-SYNC WI-FI TECHNOLOGY

Change messages locally using your smartphone Safely change messages away from traffic.

ROBUST TRAILER DESIGN

Tongue wheel jack for safe and easy set up Controller located away from the road Rugged indexed rod mast brake

FULLY-INTEGRATED CELLULAR 4G LTE MODEM

No 3G upgrade needed 10-year fleet cell service Cell plan for smart work zones (optional)

JAMLOGIC® SOFTWARE

Hourly automated refresh and battery/GPS alerts & reports

Interactive map & list view of all equipment Project folders to organize equipment Logs date/time of all activated messages

APPLICATIONS

- City and county (urban areas)
- School zones
- Special events



3 WAYS TO CHANGE A MESSAGE



ON THE SIGNUsing our V-Touch Controller



NEAR THE SIGNUsing our V-SYNC Wi-Fi



REMOTELY

Using JamLogic® Web on your computer, tablet or smartphone





POWER SUPPLY CONFIGURATION

SOLAR PANELS

Provide maximum solar recharging year-round

• Designed to run 12 months in most regions without manual recharging

HIGH-QUALITY CONSTRUCTION

SUPERIOR POWDER COATING FINISH

Impact, humidity, salt spray and rust resistant

4 ADJUSTABLE STABILIZER LEGS

Stabilization and easy transportation

TONGUE WHEEL JACK

Easy, safe trailer set up

MANUAL LIFT MECHANISM

For a quick deployment

RUGGED INDEXED ROD MAST BRAKE

The sign can be positioned at 209° (17° increments)

LOCKABLE PLASTIC BOX

Controller, modem and other components protection

2-IN. (51 MM) COUPLER OR 3-IN. (76 MM) **PINTLE EYE**

For easy towing

REMOVABLE TONGUE

Saves space for storage

V-TOUCH CONTROLLER

NTCIP* COMPLIANT

EASY-TO-READ

7-inch (178 mm) color LCD touchscreen display screen

USER-FRIENDLY

One-click icon-based menu items

TIME-SAVING

Create your own library of messages

SIMPLE TO OPERATE

Intuitive point-and-go icons make displaying and editing messages quick and easy to display

ADDITIONAL FUNCTIONALITIES

Scheduling, sign diagnostics, pin-protected security, and much more



DISPLAY

- Display panel: 45 x 80 in. (1142 x 2026 mm)
- Full-matrix of 30 x 56 pixels
- 2 LEDs per pixel
- 3 lines of 9 characters per line (5 x 7 default font)
- Up to 3 lines of 13 characters per line $(3 \times 7 \text{ font})$
- Plug-and-play display modules for simplified maintenance

DIMENSIONS AND WEIGHT

- Overall length: 133 in. (3367 mm)
- Overall width: 70 in. (1788 mm)
- Traveling height: 91 in. (2308 mm)
- Operating height: 133 in. (3387 mm)
- Weight (approx.): 1260 lb (571 kg)
- Axle/suspension: 2000 lb (909 kg)



OPTIONS

- Battery charger
- Radar
- Traffic data (requires radar)
- Rear leveling swivel jacks
- Tilt-and-rotate solar panels

Other options are available to meet your needs.

WARRANTY

- 1 year on complete trailer
- 2 years on electronic components manufactured by Ver-Mac







