

## SAFETY DATA SHEET

# GLOSS

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Trade name

GLOSS

Product no.

v

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Waterbased paint for indoor use.

Uses advised against

None known.

### 1.3. Details of the supplier of the safety data sheet

Company and address

**Bleo Aps**

Kastelsvej 17, 4. tv.

2100 København Ø.

Denmark

+45 60154830/+45 29243421

Contact person

Camilla Madsen

E-mail

cama@bleocollective.com

Revision

08/11/2023

SDS Version

1.0

### 1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Not classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

### 2.2. Label elements

Hazard pictogram(s)

Not applicable.

Signal word

Not applicable.

Hazard statement(s)

Not applicable.

Precautionary statement(s)

General

-

Prevention

-

Response

-

Storage

-

Disposal

-

Hazardous substances

None known.

**Additional labelling**

EUH208, Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 1,2-benzisothiazol-3(2H)-on. May produce an allergic reaction.

EUH210, Safety data sheet available on request.

The product contains a biocidal product.

**VOC**

VOC content: 70 g/L

MAXIMUM VOC CONTENT (Phase II, category A/d (WB): 130 g/L)

**2.3. Other hazards**

**Additional warnings**

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

**SECTION 3: Composition/information on ingredients**

**3.1. Substances**

Not applicable. This product is a mixture.

**3.2. Mixtures**

Product/substance	Identifiers	% w/w	Classification	Note
Titandioxid	CAS No.: 13463-67-7 EC No.: 236-675-5 UK-REACH: Index No.:	15-25%		
propane-1,2-diol	CAS No.: 57-55-6 EC No.: 200-338-0 UK-REACH: Index No.:	5-10%		
2-(2-butoxyethoxy)ethanol	CAS No.: 112-34-5 EC No.: 203-961-6 UK-REACH: Index No.: 603-096-00-8	1-3%	Eye Irrit. 2, H319	[1], [3]
1,2-benzisothiazol-3(2H)-on	CAS No.: 2634-33-5 EC No.: 220-120-9 UK-REACH: Index No.: 613-088-00-6	<0.05%	Acute Tox. 4, H302 Skin Irrit. 2, H315 Skin Sens. 1, H317 (SCL: 0.036 %) Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411	
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	CAS No.: 55965-84-9 EC No.: UK-REACH: Index No.: 613-167-00-5	<0.0015%	EUH071 Acute Tox. 3, H301 Acute Tox. 2, H310 Skin Corr. 1C, H314 (SCL: 0.60 %) Skin Sens. 1A, H317 (SCL: 0.0015 %) Acute Tox. 2, H330 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=10)	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

**Other information**

[1] European occupational exposure limit.

[3] According to UK REACH, Annex XVII, the substance is subject to restrictions.

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

#### Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

#### Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

#### Eye contact

If in eyes: Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Remove contact lenses. Seek medical assistance and continue flushing during transport.

#### Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

#### Burns

Not applicable.

#### 4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact.

Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

#### Information to medics

Bring this safety data sheet or the label from this product.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO<sub>2</sub>)

#### 5.3. Advice for firefighters

Fire fighters should wear appropriate personal protective equipment.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation, especially in confined areas.

Contaminated areas may be slippery.

#### 6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

Keep unauthorized persons away from the spill

#### 6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

#### 6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

### SECTION 7: Handling and storage

7.1. Precautions for safe handling

Smoking, drinking and consumption of food is not allowed in the work area.  
See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material

Always store in containers of the same material as the original container.

Storage temperature

No specific requirements

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Titandioxid

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 10(inhalable)/4(respirable)

propane-1,2-diol

Long term exposure limit (8 hours) (ppm): 150(total)

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 474(total)/10(particulates)

2-(2-butoxyethoxy)ethanol

Long term exposure limit (8 hours) (ppm): 10

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 67,5

Short term exposure limit (15 minutes) (ppm): 15

Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 101,2

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.  
EH40/2005 Workplace exposure limits (Fourth Edition 2020).

DNEL

2-(2-butoxyethoxy)ethanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	50 mg/kg/d
Long term – Systemic effects - Workers	Dermal	83 mg/kg/d
Long term – Local effects - General population	Inhalation	40,5 mg/m <sup>3</sup>
Long term – Local effects - Workers	Inhalation	67,5 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Inhalation	40,5 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	67,5 mg/m <sup>3</sup>
Short term – Local effects - General population	Inhalation	60,7 mg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	101,2 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	5 mg/kg/d

propane-1,2-diol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	213 mg/kg/day
Long term – Local effects - General population	Inhalation	10 mg/m <sup>3</sup>
Long term – Local effects - Workers	Inhalation	10 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Inhalation	50 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	168 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	85 mg/kg/day

propylidyntrimethanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	0,34 mg/kg

Long term – Systemic effects - Workers	Dermal	0,94 mg/kg
Long term – Systemic effects - General population	Inhalation	0,58 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	3,3 mg/m <sup>3</sup>
<b>Titandioxid</b>		
<b>Duration:</b>	<b>Route of exposure:</b>	<b>DNEL:</b>
Long term – Local effects - Workers	Inhalation	10 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	700 mg/kg bw/day

#### PNEC

##### 2-(2-butoxyethoxy)ethanol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater	-	1,1 mg/l
Freshwater sediment	-	4,4 mg/kg
Intermittent release	-	11 mg/l
Marine water	-	0,11 mg/l
Marine water sediment	-	0,44 mg/kg
Sewage treatment plant	-	200 mg/l
Soil	-	0,32 mg/kg

##### propane-1,2-diol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater	-	260 mg/l
Freshwater sediment	-	572 mg/kg
Intermittent release	-	183 mg/L
Marine water	-	26 mg/L
Marine water sediment	-	57,2 mg/kg
Sewage treatment plant	-	20000 mg/L
Soil	-	50 mg/kg

##### Titandioxid

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater	-	0,184 mg/l
Freshwater sediment	-	1000 mg/l
Intermittent release	-	0,193 mg/l
Marine water	-	0,0184 mg/l
Marine water sediment	-	100 mg/Kg
Sewage treatment plant	-	100 mg/l
Soil	-	100 mg/l

## 8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

### General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

### Exposure scenarios

There are no exposure scenarios implemented for this product.

### Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

### Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

### Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

**Measures to avoid environmental exposure**


No specific requirements.

**Individual protection measures, such as personal protective equipment**


**Generally**

Use only UKCA marked protective equipment.


**Respiratory Equipment**

Work situation	Type	Class	Colour	Standards	
Spray Application	Combination filter A2P3	Class 2/3	Brown/White	EN14387	

**Skin protection**

Recommended	Type/Category	Standards	
Dedicated work clothing should be worn. Wear a protective suit in the event of prolonged periods of work with the product.	-	-	

**Hand protection**

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	0.4	> 480	EN374-2, EN374-3, EN388	

**Eye protection**

No specific requirements.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

**Physical state**

Liquid

**Colour**

Not applicable

**Odour / Odour threshold**

Characteristic

**pH**

Testing not relevant or not possible due to the nature of the product.

**Density (g/cm<sup>3</sup>)**

1,2

**Kinematic viscosity**

Testing not relevant or not possible due to the nature of the product.

**Particle characteristics**

Does not apply to liquids.

**Phase changes**

**Melting point/Freezing point (°C)**

Testing not relevant or not possible due to the nature of the product.

**Softening point/range (waxes and pastes) (°C)**

Does not apply to liquids.

**Boiling point (°C)**

Testing not relevant or not possible due to the nature of the product.

**Vapour pressure**

Testing not relevant or not possible due to the nature of the product.

**Relative vapour density**

Testing not relevant or not possible due to the nature of the product.

**Decomposition temperature (°C)**

Testing not relevant or not possible due to the nature of the product.

Data on fire and explosion hazards

Flash point (°C)

Testing not relevant or not possible due to the nature of the product.

Flammability (°C)

Testing not relevant or not possible due to the nature of the product.

Auto-ignition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

Lower and upper explosion limit (% v/v)

Testing not relevant or not possible due to the nature of the product.

Solubility

Solubility in water

Completely soluble

n-octanol/water coefficient

Testing not relevant or not possible due to the nature of the product.

Solubility in fat (g/L)

Testing not relevant or not possible due to the nature of the product.

9.2. Other information

VOC (g/l)

70

Oxidizing properties

Testing not relevant or not possible due to the nature of the product.

Other physical and chemical parameters

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 as retained and amended in UK law

Acute toxicity

Product/substance	Titandioxid
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	>5000 mg/Kg ·

Product/substance	Titandioxid
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50
Result:	> 3,43 - 5,09 mg/l ·

Product/substance	propane-1,2-diol
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	22000 mg/kg ·

Product/substance	propane-1,2-diol
Species:	Rabbit

Route of exposure: Test: Result:	Dermal LD50 2000 mg/kg ·
Product/substance Species: Route of exposure: Test: Result:	propane-1,2-diol Rabbit Inhalation LC50 317 mg/l ·
Product/substance Species: Route of exposure: Test: Result:	2-(2-butoxyethoxy)ethanol Rat Oral LD50 5660 mg/kg ·
Product/substance Species: Route of exposure: Test: Result:	2-(2-butoxyethoxy)ethanol Rabbit Dermal LD50 2700 mg/kg ·
Product/substance Species: Route of exposure: Test: Result:	2-(2-butoxyethoxy)ethanol Mouse Oral LD50 2400 mg/kg ·
Product/substance Species: Route of exposure: Test: Result:	1,2-benzisothiazol-3(2H)-on Rat Oral LD50 1193 mg/Kg ·
Product/substance Species: Route of exposure: Test: Result:	1,2-benzisothiazol-3(2H)-on Rat Dermal LD50 4115 mg/Kg ·
Product/substance Species: Route of exposure: Test: Result:	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) Rat Oral LD50 49,6 - 75 mg/Kg ·
Product/substance Species: Route of exposure: Test: Result:	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) Rat Inhalation LC50 0,33 mg/l, 4 h, aerosol ·
Product/substance Species: Route of exposure: Test: Result:	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) Rabbit Dermal LD50 200 - 1000 mg/Kg ·
<b>Skin corrosion/irritation</b>	
Product/substance Test method: Species: Result:	1,2-benzisothiazol-3(2H)-on OECD 404 Rabbit Adverse effect observed (Irritating)
<b>Serious eye damage/irritation</b>	
Product/substance Test method: Result:	1,2-benzisothiazol-3(2H)-on no guideline followed Adverse effect observed (Causes serious eye damage)



### Respiratory sensitisation

Based on available data, the classification criteria are not met.

### Skin sensitisation

Product/substance	1,2-benzisothiazol-3(2H)-on
Species:	Human
Result:	Adverse effect observed (sensitising)
Other information:	Can course allergic reaction at skin contact

Product/substance	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Species:	Human
Result:	Adverse effect observed (sensitising)
Other information:	Can course allergic reaction at skin contact

### Germ cell mutagenicity

Product/substance	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Conclusion:	No adverse effect observed

### Carcinogenicity

Product/substance	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Conclusion:	No adverse effect observed

### Reproductive toxicity

Product/substance	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Conclusion:	No adverse effect observed

### STOT-single exposure

Based on available data, the classification criteria are not met.

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

### Aspiration hazard

Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### Long term effects

None known.

### Endocrine disrupting properties

This mixture/product does not contain any substances considered to have hormone-disrupting properties in relation to health.

### Other information

Titandioxid has been classified by IARC as a group 2B carcinogen.

## SECTION 12: Ecological information

### 12.1. Toxicity

Product/substance	Titandioxid
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	>1000 mg/l ·

Product/substance	Titandioxid
Species:	Daphnia
Duration:	48 hours
Test:	EC50
Result:	>1000 mg/l ·

Product/substance	Titandioxid
Species:	Algae
Duration:	72 hours
Test:	EC50
Result:	61 mg/l ·

Product/substance	propane-1,2-diol
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	> 40613 mg/l ·

Product/substance	propane-1,2-diol
Species:	Daphnia
Duration:	48 hours
Test:	EC50
Result:	18800 mg/l ·
Product/substance	propane-1,2-diol
Species:	Algae
Duration:	96 hours
Test:	EC50
Result:	19000 mg/l ·
Product/substance	propane-1,2-diol
Species:	Algae
Duration:	72 hours
Test:	EC50
Result:	24200 mg/l ·
Product/substance	2-(2-butoxyethoxy)ethanol
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	2700 mg/l ·
Product/substance	2-(2-butoxyethoxy)ethanol
Species:	Daphnia
Duration:	48 hours
Test:	LC50
Result:	1000 mg/l ·
Product/substance	2-(2-butoxyethoxy)ethanol
Species:	Algae
Duration:	96 hours
Test:	EC50
Result:	100 mg/l ·
Product/substance	1,2-benzisothiazol-3(2H)-on
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	1,3 mg/l ·
Product/substance	1,2-benzisothiazol-3(2H)-on
Species:	Daphnia
Duration:	96 hours
Test:	EC50
Result:	1,5 mg/l ·
Product/substance	1,2-benzisothiazol-3(2H)-on
Species:	Algae
Duration:	48 hours
Test:	EC50
Result:	0,055 mg/l ·
Product/substance	1,2-benzisothiazol-3(2H)-on
Species:	Daphnia
Duration:	48 hours
Test:	EC50
Result:	2,94 mg/l ·
Product/substance	1,2-benzisothiazol-3(2H)-on
Species:	Algae
Duration:	24 hours
Test:	EC50
Result:	0,11 mg/l ·

Product/substance	1,2-benzisothiazol-3(2H)-on
Species:	Fish
Duration:	No data available.
Test:	NOEC
Result:	0,21 mg/l ·
Product/substance	1,2-benzisothiazol-3(2H)-on
Species:	Daphnia
Duration:	21 days
Test:	NOEC
Result:	1,2 mg/l ·
Product/substance	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	0,19 mg/l ·
Product/substance	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Species:	Daphnia
Duration:	48 hours
Test:	EC50
Result:	0,10 mg/l ·
Product/substance	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Species:	Algae
Duration:	72 hours
Test:	EC50
Result:	0,048 mg/l ·
Product/substance	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Species:	Algae
Duration:	96 hours
Test:	NOEC
Result:	0,032 mg/l ·
Product/substance	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Species:	Daphnia
Duration:	21 days
Test:	EC50
Result:	> 1 mg/l ·
Product/substance	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	0,58 mg/l ·
Product/substance	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Species:	Fish
Duration:	34 d.
Test:	NOEC
Result:	0,5 mg/l ·
Product/substance	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Species:	Algae
Duration:	48 hours
Test:	NOEC
Result:	0,00064 mg/l ·
Product/substance	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Species:	Daphnia
Duration:	21 days
Test:	NOEC
Result:	0,004 mg/l ·

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)  
 Species: Fish  
 Duration: 28 days  
 Test: NOEC  
 Result: 0,098 mg/l

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)  
 Species: Algae  
 Duration: 72 hours  
 Test: NOEC  
 Result: 0,0012 mg/l

**12.2. Persistence and degradability**

Product/substance propane-1,2-diol  
 Biodegradable: Yes  
 Result: BOD5/COD > 0,5

Product/substance 1,2-benzisothiazol-3(2H)-on  
 Biodegradable: Yes

**12.3. Bioaccumulative potential**

Product/substance propane-1,2-diol  
 Potential bioaccumulation: No  
 LogPow: -1,4000  
 BCF: 0,09

Product/substance 1,2-benzisothiazol-3(2H)-on  
 Potential bioaccumulation: No  
 LogPow: 1,3000  
 BCF: No data available.

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)  
 Potential bioaccumulation: No  
 LogPow: 0,4000  
 BCF: 3,6

**12.4. Mobility in soil**

No data available.

**12.5. Results of PBT and vPvB assessment**

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

**12.6. Endocrine disrupting properties**

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

**12.7. Other adverse effects**

None known.

**SECTION 13: Disposal considerations**

**Waste treatment methods**

Product is not covered by regulations on dangerous waste.  
 Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

**EWC code**

08 01 12 Waste paint and varnish other than those mentioned in 08 01 11

**Specific labelling**

**Contaminated packing**

**SECTION 14: Transport information**

	<b>14.1 UN / ID</b>	<b>14.2 UN proper shipping name</b>	<b>14.3 Hazard class(es)</b>	<b>14.4 PG*</b>	<b>14.5 Env**</b>	<b>Other information:</b>
ADR	-	-	-	-	-	-
IMDG	-	-	-	-	-	-

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
IATA	-	-	-	-	-	-

\* Packing group

\*\* Environmental hazards

**Additional information**

Not dangerous goods according to ADR, IATA and IMDG.

**14.6. Special precautions for user**

Not applicable.

**14.7. Maritime transport in bulk according to IMO instruments**

No data available.

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Restrictions for application**

No special.

**Demands for specific education**

No specific requirements.

**SEVESO - Categories / dangerous substances**

Not applicable.

**Additional information**

Not applicable.

**Sources**

In accordance with Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products as retained and amended in UK law.

2012 No. 1715 ENVIRONMENTAL PROTECTION: The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

**15.2. Chemical safety assessment**

No

**SECTION 16: Other information**

**Full text of H-phrases as mentioned in section 3**

EUH071, Corrosive to the respiratory tract.

H301, Toxic if swallowed.

H302, Harmful if swallowed.

H310, Fatal in contact with skin.

H314, Causes severe skin burns and eye damage.

H315, Causes skin irritation.

H317, May cause an allergic skin reaction.

H318, Causes serious eye damage.

H319, Causes serious eye irritation.

H330, Fatal if inhaled.

H400, Very toxic to aquatic life.

H410, Very toxic to aquatic life with long lasting effects.

H411, Toxic to aquatic life with long lasting effects.

**Abbreviations and acronyms**

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EINECS = European Inventory of Existing Commercial chemical Substances  
ES = Exposure Scenario  
EUH statement = CLP-specific Hazard statement  
EuPCS = European Product Categorisation System  
EWC = European Waste Catalogue  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
IARC = International Agency for Research on Cancer (IARC)  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
OECD = Organisation for Economic Co-operation and Development  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail  
RRN = REACH Registration Number  
SCL = A specific concentration limit  
SVHC = Substances of Very High Concern  
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure  
STOT-SE = Specific Target Organ Toxicity - Single Exposure  
TWA = Time weighted average  
UN = United Nations  
UVBC = Unknown or variable composition, complex reaction products or of biological materials  
VOC = Volatile Organic Compound  
vPvB = Very Persistent and Very Bioaccumulative

**Additional information**

Not applicable.

**The safety data sheet is validated by**

MIJ

**Other**

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en