



# OWS SuperTurbo SAE 15W-40

*Universal Engine Oil for Diesel and Gasoline Engines*

## **Product Description:**

OWS SuperTurbo SAE 15W-40 is an advanced universal engine oil for diesel and gasoline engines. It's high viscosity stability protects against friction, heat and corrosion, keeping engines healthy and efficient.

OWS SuperTurbo SAE 15W-40 is manufactured in accordance to modern specifications using the highest quality base stocks and state of the art Überclean® additive technology. This ensures a finished product with an unmatched performance level.

## ***OWS SuperTurbo SAE 15W-40 fulfills or exceeds the following specifications:***

- API SN/CF
- ACEA A3/B3/B4
- VW50101/50500
- MB 229.1

Test	Method	Unit	Result
Density @ 15°C	ASTM D4052	kg/L	0.865
Kinematic Viscosity @40°C	ASTM D445	cSt	106
Kinematic Viscosity @100°C	ASTM D445	cSt	14.27
Viscosity Index	ASTM D2270		137
Flash Point, COC	ASTM D92-05A	°C	> 240
Pour Point	ASTM D97	°C	< -40

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.