

OWS 220 Engine Protector

Product Description:

Improve oil consistency
 Economical by stopping lost of oil minimize oil consumption
 Coasts and protects engines
 Reduces friction wear
 Extremely slippery under high temperature and pressure
 Prevents corrosions and sludge build up

Uses:

- For longer engine life
- Improve fuel economy
- Quilter operations
- Superior performance

Analysis Result

| <i>Characteristic</i> | <i>Units</i> | <i>ASTM Method</i> | <i>Test Result</i> |
|------------------------------|---------------------|---------------------------|---------------------------|
| Appearance | - | Visual | B & C |
| color | - | D 1500 | <3.0 |
| Density @ 15 °C | kg/l | D 4052 | 0.8996 |
| Density @ 20 °C | kg/l | D 4052 | 0.8964 |
| Density @ 30 °C | kg/l | D 4052 | 0.8901 |
| Kinematic Viscosity @ 40 °C | cSt | D 445 | 378.5 |
| Kinematic Viscosity @ 100 °C | cSt | D 445 | 27.28 |
| Viscosity Index | - | D 2270 | 98 |
| Flash Point COC | °C | D 92 | 248 |
| Pour Point | °C | D 97 | -6 |

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.