



Ecoplus SAE 5W-30

HC Synthetic Engine Oil for All Modern Cars

Product Description:

Ecoplus SAE 5W-30 is a high-tech synthetic formulation, low-viscosity engine oil that protects against friction, heat and corrosion keeping engines healthy and efficient. OWS überclean additives reduces carbon and sludge build-up even under severe driving conditions.

Ecoplus SAE 5W-30 is specially formulated for all engines to be used in Tropical Climates. Strengthened with OVS Synthetic oil additives to provide superior engine wear protection and heat tolerance compared with regular synthetic oils in the market.

Feature and Benefits:

- Maintains HP and torque, smoother and quieter engine running
- Lower friction with strengthened oil film
- Reduced CO2 emissions and improved fuel economy
- Lower emissions

Specifications :

ACEA A3 / B3 / B4;

API SL / CF;

Typical Properties:

SAE Grade: 5W30

Test	Method	Unit	Result
Density @ 15°C	ASTM D4052-09	kg / L	0.875
Kinematic Viscosity @40°C	ASTM D445-10	cSt	73.22
Kinematic Viscosity @100°C	ASTM D445-10	cSt	12.9
Viscosity Index	ASTM D2270-04		157
Flash Point, COC	ASTM D92-05a (10)	°C	231
Pour Point	ASTM D97-09	°C	- 38
Base Number	ASTM D2896-07a	mg KOH/g	7.05

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.