TECHNICAL DATA SHEET



OWS Evotec RS 5W-40

Fully Synthetic Engine Oil Recommended for Fuel Saving Urban Driving

Product Description:

OWS Evotec RS 5W-40 is a fully synthetic ester based formulation that protects against friction, heat and corrosion, keeping engines healthy and efficient. OWS überclean® additives reduces carbon or sludge build-up even under severe driving conditions. Top-class, fully synthetic fuel-economy multi-grade motor oil. Excellently suited for use in passenger car gasoline and diesel engines, both turbo-charged and non-turbo-charged.

- Increased hp and torque, Super smooth & quieter engine
- Improved fuel economy
- Lower emissions and exceeds Euro IV specs
- Almost zero engine wear with constant usage

Specifications:

API SP, ACEA A3/B4, BMW Longlife-01, MB 229.5 Porsche A40, PSA B71 2296, VW 502 00/505 00

Typical Properties:

SAE Grade: SAE 5W-40

PROPERTIES	METHOD	UNIT	TYPICAL
Density @ 15°C	ASTM D4052	kg/L	0.83
Kinematic Viscosity @40°C	ASTM D445	cSt	86
Kinematic Viscosity @100°C	ASTM D445	cSt	13.5
Viscosity Index	ASTM D2270		167.9
Flash Point, COC	ASTM D92-05a	°C	> 198
Pour Point	ASTM D97	°C	< -45

Typical properties are typical of those obtained with normal production tolerance and do no constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.