TECHNICAL DATA SHEET



OWS Evotec SAE 5W-40 D

Fully Synthetic Specially for Gasoline & Diesel Engines

Product Description:

Fully Synthetic Specially for Gasoline & Diesel Engines - OWS Evotec is a Premium multi-garde fully HC-Synthetic based formulation that protects against friction, heat and corrosion, keeping engines healthy and efficient. OWS überclean@ additives reduce carbon and sludge build-up even under severe driving conditions. Suitable for use in passenger car gasoline and diesel engines of the latest generation.

Feature and Benefits:

- Increased hp and torque, Super smooth & quieter engine
- Improved fuel economy
- Lower emissions and exceeds Euro IV specs
- · Almost zero engine wear with constant usage

Specifications:

ACEA A3/B4; API SN/CF; BMW Longlife-01; MB 229.5; Porsche A40; Renault RN0700/0710; VW 502 00 / 505 00

Test	Method	Unit	Result
Density @ 15°C	ASTM D4052	kg/L	0.75
Kinematic Viscosity @40°C	ASTM D445	cSt	86.4
Kinematic Viscosity @100°C	ASTM D445	cSt	13.8
Viscosity Index	ASTM D2270		168.4
Flash Point, COC	ASTM D92-05A	°C	> 200
Pour Point	ASTM D97	°C	< -45.7

Typical properties are typical of those obtained with normal production tolerance and do no constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.