



Safety Data Sheet According to 1907/2006/EC, Article 31

Printing Date 25.03.2022 - Revision 25.03.2022

1. Identification of Product and Company's Name:

PRODUCT DETAIL

Trade Name: OWS Multilight LXI SAE 10W-40

Article Number: SAE 10W-40

Application of the substance / the preparation:

Manufacturer / Supplier:

Our Workshop System (S) Pte Ltd
107 Tuas View Walk 1, Singapore 637730

Tel: +65 6452 3209

Fax: +65 6452 0586

www.ows-asia.com

Further information obtainable from:

Labor: Gordon Chiew

Tel: (65) 9818 3860

E-mail: info@ows-asia.com

Information in case emergency: Tel: (49) 171 9978 792 Monday to Friday 9:00 to 18:00 CET

2. Possible Hazards:

Hazard designation:

The product does not require a hazard warning label in accordance with EC directives/ GefStoffV (German regulations on dangerous substances).

3. Composition/Ingredients:

Preparation Description Highly refined mineral oils and additives

CAS	Chemical Identity	Hazard Class	Hazard Statement	% wt
64742-65-0	Base Oil	Skin Corr, 2 Eye Dam, 1	H302, H332	>85
68649-42-3	Additives	Skin Corr.2 Eye Dam, 1	H315; H318; H411	<15

UN No. : Not applicable

Additional Information : The highly refined mineral oil contain <3% (WW)
DMSO- extract, according to IP346

4. First Aid Measures:

General information Remove contaminated clothing immediately and dispose of safely.
After skin contact In case of contact with skin wash off immediately with plenty of water.
After eye contact In case of contact with the eyes rinse thoroughly with plenty of water or with an eye-cleaning solution. In case of irritation consult an oculist.
After ingestion Do not induce vomiting.
Rinse out mouth and give plenty of water to drink.
Summon a doctor immediately.

5. Fire Fighting Procedure:

Suitable extinguishing media: Foam, Dry powder, Carbon dioxide

Extinguishing media that must not be used for safety reasons : Full water jet

Special exposure hazards arising from the substance or preparation itself, its combustion products or from resulting gases:

In the event of fire the following can be released:

Carbon monoxide (CO)

Carbon dioxide (CO₂)

In case of combustion evolution of dangerous gases possible.

Special protective equipment for firefighting:

Do not inhale explosion and/or combustion gases.

Use self-contained breathing apparatus.

Other information:

Cool endangered containers with water spray jet.

6. Steps to be Taken in Case of Spill or Leak:

Personal precautions : Use personal protective clothing.

Environmental precautions : Do not discharge into the drains/surface waters/groundwater.

Methods for cleaning up/taking up : Take up with absorbent material (eg sand, kieselguhr, universal binder).
Dispose of absorbed material in accordance with the regulations.

7. Storage and Handling:

Handling

Advice on safe handling

Use personal protective clothing.

Open and handle container with care.

Avoid formation of aerosols.

Advice on protection against fire and explosion

No special measures necessary.

Storage

Requirements for storage rooms and vessels

Protect from frost.

Protect from heat and direct sunlight.

Keep container tightly closed.

8. Explosion Control/Personal Protection:

Additional hints on technical system design.

See chapter 7; no measures exceeding the ones mentioned are necessary.

Ingredients with occupational exposure limits to be monitored

EINECS-No. Name Type Value Unit

Personal protective equipment

Respiratory protection

Breathing apparatus in the event of aerosol or mist formation.

Hand protection

Recommendation: Impermeable safety gloves made of nitrile as per EN 374; penetration time more than 480 min. at a thickness of 0.4 mm.

Eye protection

Safety glasses with side protection shield

General protective measures

Do not inhale gases/vapours/aerosols.

Avoid contact with eyes and skin.

At work do not eat, drink, smoke or take drugs.

Keep away from foodstuffs and beverages.

Wash hands before breaks and after work.

9. Physical & Chemical Characteristics:

Form: liquid	Color: ASTM colour code : 2.5		Odor: Typical
	Value	Unit	Method
Flammability	Not under normal conditions		
Ignition Temperature	>300	°C	DIN 51 794
Auto-ignition	None		
Explosion danger	under strong heat and/or excessive misting only		
Explosion limit			
Lower limit	0.6	Vol. %	
Upper limit	6.5	Vol. %	
Density at T=15°C	0.85 – 0.88	g/cm ³	ISO 3675
Solubility in 20°C water	practically insoluble		
Viscosity (cinematic)			
T = 40°C		mm ² /s	DIN 51 562
T = 100°C	12.5-16.3	mm ² /s	DIN 51 562
Flash Point	>200	°C	ISO 2592
Pour Point	< -30	°C	ISO 3016
Vapour Pressure (20°C)	< 1	hPa	Literature

10. Stability & Reactivity Data:

Materials to avoid
Reactions with strong oxidising agents.
Hazardous decomposition products
No hazardous reactions when stored and handled according to prescribed instructions.

11. Toxicological Information:

General remarks

No toxicological data are available.
Experience in practice
Keeping to the general worker's protection rules and the industrial hygienics,
there is no risk in handling this product through the personnel.

12. Ecological Information:

Do not discharge into the drains/surface waters/groundwater.
The formulation was evaluated using the conventional method of the Dangerous Preparations Directive 1999/45/EC and not classified as hazardous to the environment.

13. Disposal Instructions:

Waste code: 130205 mineral-based non-chlorinated engine, gear and lubricating oils The listed waste code numbers, according to the European Waste Catalogue (EWC), are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company.

Uncleaned packaging

Uncontaminated packaging may be taken for recycling.
Packaging that cannot be cleaned should be disposed off in agreement with the regional waste disposal company.

14. Transportation Instructions:

"Product is not subject to the regulations for dangerous goods".

15. Regulation Instructions:

Labeling in accordance with EC directives

The product does not require a hazard warning label in accordance with EC directives/ GefStoffV (German regulations on dangerous substances).

National Regulations

Water hazard class / source 2 (

VwVwS)

TA-Luft / paragraph (for Germany only):

Class III

VbF (Germany) : -

16. Other Information:

38 Irritating to skin.

41 Risk of serious damage to eyes.

The data mentioned in the present safety data sheet correspond to our latest knowledge and experience and may be used to precise safety requirements for the different products. The information given therein is no warranty as to quality.

Please also read our technical data sheet.

n.a.: no applicable

n.b.: no determined