



OVS Synthoil HC SAE 10W-40

Semi-Synthetic Universal Engine Oil for Diesel and Gasoline Engines with or without Turbo

Product Description:

OVS Synthoil HC SAE 10W-40 is a Fuel-Economy motor oil based on synthetic base stocks. OVS Überclean® additive technology reduces carbon and sludge build-up even under severe driving conditions.

OVS Synthoil HC SAE 10W-40 is suitable for for latest generation of gasoline and diesel engine passenger cars, both turbo-charged and non-turbo-charged.

OVS Synthoil HC SAE 10W-40 fulfills or exceeds the following specifications:

- ACEA A3 / B3 / B4
- API SM/CF
- MB 229.3
- Renault RN 0700
- BMW Longlife-98
- VW 502 00 / 505 00

Test	Method	Unit	Result
Density @ 15°C	ASTM D4052-09	kg / L	0.860
Kinematic Viscosity @40°C	ASTM D445-10	cSt	88.6
Kinematic Viscosity @100°C	ASTM D445-10	cSt	14.1
Viscosity Index	ASTM D2270-04		164
Flash Point, COC	ASTM D92-05A(10)	°C	210
Pour Point	ASTM D97-09	°C	-35

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.