TECHNICAL DATA SHEET



OWS Synthor SAE 10W-30

HC-Synthetic High Performance Engine Oil for Modern Gasoline and Diesel Engines

Product Description:

OWS Synthor SAE 10W-30 is a high-performance light-running HC-Synthetic engine oil designed for use in modern engines. It delivers excellent performance and fuel economy properties.

OWS Synthor SAE 10W-30 is manufactured using the highest quality HC-Synthetic base oils and state of the art Überclean® additive technology. This ensures a finished product with an unmatched performance level.

OWS Synthor SAE 10W-30 is an ideal choice for most gasoline and diesel engines, including turbocharged and non-turbo-charged engines, and can be used year round in most climates.

OWS Synthor SAE 10W-30 fulfils or exceeds the following specifications:

ACEA A3 / B3 / B4 API SN/CF MB 229.1 VW 501 01 / 505 00

Test	Method	Unit	Result
Density @ 15°C	ASTM D1500		< 3.5
Kinematic Viscosity @40°C	ASTM D4052	kg/L	0.863
Kinematic Viscosity @100°C	ASTM D445	cSt	67.5
Viscosity Index	ASTM D445	cSt	12.5
Flash Point, COC	ASTM D2270		144
Pour Point	ASTM D92-05A	°C	> 230
	ASTM D97	°C	<-35

Typical properties are typical of those obtained with normal production tolerance and do no constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to