



# OWS Synthotec SAE 0W-30 LV II

*Advanced High Performance Fully Synthetic Engine Oil*

## **Product Description:**

OWS Synthotec SAE 0W-30 LV II is a fully synthetic ester based formulation that protects against friction, heat and corrosion, keeping engines healthy and efficient. OWS Überclean® additives reduce carbon and sludge build-up under severe driving conditions.

OWS Synthotec SAE 0W-30 LV II was developed for, and in conduction with, VW/AUDI engines with extended drain intervals including engines with pump nozzle technology.

***OWS Synthotec SAE 0W-30 LV II fulfils or exceeds the following specifications:***

API SN/CF  
VW50300/50600/50601

Test	Method	Unit	Result
Density @ 15°C	ASTM D4052-09	kg/L	0.839
Kinematic Viscosity @40°C	ASTM D445-10	cSt	72.0
Kinematic Viscosity @100°C	ASTM D445-10	cSt	12.5
Viscosity Index	ASTM D2270-04		174
Flash Point, COC	ASTM D92-05A(10)	°C	> 210
Pour Point	ASTM D97-09	°C	< -52

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.