



OWS Synthomax SAE 0W-30

Fully Synthetic Universal Engine Oil for Diesel and Gasoline Engines

Product Description:

OWS Synthomax SAE 0W-30 is a Top-Class multi-grade fully synthetic ester based formulation that protects against friction, heat and corrosion, keeping engines healthy and efficient. OWS Übercleal additives reduce carbon and sludge build-up even under severe driving conditions.

OWS Synthomax SAE 0W-30 is excellently suited for use in passenger car gasoline and diesel engines, both turbo-charged and non-turbo-charged.

OWS Synthomax SAE 0W-30 fulfils or exceeds the following specifications:

- ACEAA3 / B4
- API SN/CF
- VW50500/50500
- BMW Longlife-01 MB 229.3
- PSA B71 2296

Test	Method	Unit	Result
Density @ 15°C	ASTM D4052-09	kg/L	0.845
Kinematic Viscosity @40°C	ASTM D445-10	cSt	72.0
Kinematic Viscosity @100°C	ASTM D445-10	cSt	12.5
Viscosity Index	ASTM D2270-04		174
Flash Point, COC	ASTM D92-05A(10)	°C	> 200
Pour Point	ASTM D97-09	°C	< -50

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.