



OWS Synthomax ULTIMATE SAE 0W-40

Fully Synthetic High Performance Multigrade Engine Oil

Product Description:

OWS Synthomax ULTIMATE SAE 0W-40 is a fully synthetic PAO based formulation that protects against friction, heat and corrosion, keeping engines healthy and efficient.

OWS überclean® additives reduces carbon or sludge build up even under severe driving conditions. Top-class fully synthetic fuel-economy multi-grade motor oil.

Specifications :

ACEA A3 / B4; API SP

BMW LL-01

MB 229.5

PSA B71 2296

VW 502 00 / 505 00

Renault RN 0700 / RN 0710

Porsche A40

Typical Properties:

SAE Grade: **0W-40**

Test	Method	Unit	Result
Density @ 15°C	ASTM D4052-09	kg / L	0.854
Kinematic Viscosity @40°C	ASTM D445-10	cSt	81.7
Kinematic Viscosity @100°C	ASTM D445-10	cSt	14.2
Viscosity Index	ASTM D2270-04		180
Flash Point, COC	ASTM D92-05a (10)	°C	242
Pour Point	ASTM D97-09	°C	- 44
Base Number	ASTM D2896-07a	mg KOH/g	10.5

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.