## TECHNICAL DATA SHEET



## **OWS Tourer DLS SAE 5W-30**

Fully Synthetic Engine Oil for Diesel (DPF) and Gasoline Engines with or without Turbo

## **Product Description:**

OWS Tourer SAE 5W-30 DLS is a fully synthetic based formulation that protects against friction, heat and corrosion, keeping engines healthy and efficient. OWS Überclean® additive technology reduces carbon or sludge build up even under severe driving conditions.

OWS Tourer SAE 5W-30 DLS is manufactured using the highest quality Fully Synthetic base stocks and state of the art Überclean® additive technology. This ensures a finished product with an unmatched performance level.

OWS Tourer SAE 5W-30 DLS is designed for advanced passenger car gasoline and diesel engines, both turbocharged and non-turbo-charged including engines with diesel particle filters (ACEA C3)

OWS Tourer SAE 5W-30 DLS fulfills or exceeds the following specifications:

ACEA C3 API SN / CF BMW Longlife-04 MB 229.51 GM Dexos 2 VW 502 00 / 505 00 / 505 01

Test	Method	Unit	Result
Density @ 15°C	ASTM D4052	kg/L	0.8514
Kinematic Viscosity @40°C	ASTM D445	cSt	69.38
Kinematic Viscosity @100°C	ASTM D445	cSt	11.56
Viscosity Index	ASTM D2270		162
Flash Point, COC	ASTM D92-05A	°C	230
Pour Point	ASTM D97	°C	-45

Typical properties are typical of those obtained with normal production tolerance and do no constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.