



OWS Triton C1 SAE 5W-30

Fully Synthetic Engine Oil for Diesel and Gasoline Engines with or without Turbo

Product Description:

OWSTriton C1 SAE 5W-30 is a fully synthetic based formulation that protects against friction, heat and corrosion, keeping engines healthy and efficient. OWS Überclean® additive technology reduces carbon or sludge build up even under severe driving conditions. Optimally suited for use in Ford and Mazda vehicles equipped with diesel particle filter systems (ACEAC1)

OWSTriton C1 SAE 5W-30 is manufactured using the highest quality Fully Synthetic base oils and state of the art Überclean® additive technology. This ensures a finished product with an unmatched performance level.

OWS Triton C1 SAE 5W-30 is designed for advanced passenger car gasoline and diesel engines, both turbocharged and non-turbo-charged including engines with diesel particle filters (ACEA C1)

OWSTriton C1 SAE 5W-30 fulfills or exceeds the following specifications:

- ACEA A5/B5/C1
- Ford WSS-M2C934-C
- JASO DL-1

Test	Method	Unit	Result
Density @ 15°C	ASTM D4052	kg/L	0.850
Kinematic Viscosity @40°C	ASTM D445	cSt	55.4
Kinematic Viscosity @100°C	ASTM D445	cSt	10.0
Viscosity Index	ASTM D2270		170
Flash Point, COC	ASTM D92-05A	°C	> 220
Pour Point	ASTM D97	°C	-35

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.