TECHNICAL DATA SHEET



OWS Triton C4 SAE 5W-30

Fully Synthetic Engine Oil for Diesel and Gasoline Engines with or without Turbo

Product Description:

OWS Triton C4 SAE 5W-30 is a fully synthetic based formulation that protects against friction, heat and corrosion, keeping engines healthy and efficient. OWS Überclean® additive technology reduces carbon or sludge build up even under severe driving conditions. Optimally suited for use in Renault vehicles equipped with diesel particle filter systems (ACEA C4)

OWS Triton C4 SAE 5W-30 is manufactured using the highest quality Fully Synthetic base oils and state of the art Überclean® additive technology. This ensures a finished product with an unmatched performance level.

OWS Triton C4 SAE 5W-30 is designed for advanced passenger car gasoline and diesel engines, both turbo charged and non-turbo-charged including engines with diesel particle filters (ACEA C4)

OWS Triton C4 SAE 5W-30 fulfils or exceeds the following specifications:

ACEA C4 Renault RN 0720 MB 226.51

Test	Method	Unit	Result
Density @ 15°C	ASTM D4052	kg/L	0.854
Kinematic Viscosity @40°C	ASTM D445	cSt	68
Kinematic Viscosity @100°C	ASTM D445	cSt	11.6
Viscosity Index	ASTM D2270		166
Flash Point, COC	ASTM D92-05A	°C	> 220
Pour Point	ASTM D97	°C	< -38

Typical properties are typical of those obtained with normal production tolerance and do no constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.