



OWS Triton D SAE 5W-30

Advanced High Performance Fully Synthetic PAO Based Engine Oil

Product Description:

OWS Triton D SAE 5W-30 Fully Synthetic PAO Based formulation protects against friction, heat and corrosion, keeping engines healthy and efficient. OWS Überclean® additives reduce carbon and sludge build up even under severe driving conditions.

OWSTriton D SAE 5W-30 has an excellent range of applications. Appropriate for use in turbo-charged car giving improved engines quietness and reduced emissions. Sustained horsepower and torque throughout the life of your engine with regular use.

OWSTriton D SAE 5W-30 is manufactured using the highest quality Fully Synthetic base stocks and state of the art Überclean® technology. This ensures a finished product with an unmatched performance level.

OWSTriton D SAE 5W-30 fulfills or exceeds the following specifications:

ACEA A3 / B3 / B4; API SN / CF; BMW LL-01; MB 229.5; VW 501 01/502 00/505 00

Test	Method	Unit	Result
Density @ 15°C	ASTM D4052	kg/L	0.860
Kinematic Viscosity @40°C	ASTM D445	cSt	68
Kinematic Viscosity @100°C	ASTM D445	cSt	11.2
Viscosity Index	ASTM D2270		164
Flash Point, COC	ASTM D92-05A	°C	> 200
Pour Point	ASTM D97	°C	< -40

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.