



# OWS Triton C2 SAE 0W-30

*Fully Synthetic Low-SAPS Engine Oil for Diesel and Gasoline Engines with or without Turbo*

## **Product Description:**

OWS Triton C2 SAE 0W-30 is a fully synthetic based formulation that protects against friction, heat and corrosion, keeping engines healthy and efficient. OWS Überclean® additive technology reduces carbon or sludge build up even under severe driving conditions.

OWS Triton C2 SAE 0W-30 is manufactured using the highest quality Fully Synthetic base oils and state of the art Überclean® additive technology. The modern manufacturing process ensures a top-quality finished product.

OWS Triton C2 SAE 0W-30 is designed for advanced passenger car gasoline and diesel engines, both turbocharged and non-turbo-charged including engines with diesel particle filters (ACEA C2).

## **Specifications :**

ACEA C2; ACEA A5/B5

BMW Longlife 12FE

Fiat 9.55535-GS1/DS1

Ford M2C 950-A Peugeot/Citroen B71 2312

Test	Method	Unit	Result
Density @ 15°C	ASTM D4052	kg / L	0.838
Kinematic Viscosity @40°C	ASTM D445	cSt	58.7
Kinematic Viscosity @100°C	ASTM D445	cSt	11.9
Viscosity Index	ASTM D2270		204
Flash Point, COC	ASTM D92-05A	°C	> 225
Base Number	ASTM D97	°C	< -50
TBN	ASTM D2896	mg KOH/g	7.5
Sulphate Ash	ASTM D874-13a	% weight	0.7

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.