



# OWS Eco Max FE SAE 5W-30

*HC-Synthetic Multigrade Fuel Economy Engine Oil*

## **Product Description:**

OWS Eco Max FE SAE 5W-30 is a HC-Synthetic and PAO based formulation that protects against friction, heat and corrosion, keeping engines healthy and efficient. For use in all VW / AUDI / Seat and Skoda engines except for:R3/R4 pump nozzle technology engines without extended drain intervals and DPF, R5 pump nozzle technology engines without PDF and V10 pump nozzle technology engines without DPF up to and including model 2006.

## **Specifications :**

ACEA C3, ACEA A3/B4-04 API SN/CF, BMW Longlife-04 GM Dexos 2, MB 229.31 VW 504 00 and 507 00

## **Typical Properties:**

**SAE Grade: 5W30**

Test	Method	Unit	Result
Density @ 15°C	ASTM D4052-09	kg / L	0.85
Kinematic Viscosity @40°C	ASTM D445-10	cSt	71
Kinematic Viscosity @100°C	ASTM D445-10	cSt	12.0
Viscosity Index	ASTM D2270-04		154
Flash Point, COC	ASTM D92-05a (10)	°C	230
Pour Point	ASTM D97-09	°C	- 36
Base Number	ASTM D2896-07a	mg KOH/g	7

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.