



OWS Syntholube Ultimate SAE 10W-60

Ultra Performance Fully Synthetic Racing Engine Oil

Product Description:

OWS Syntholube Ultimate SAE 10W-60 is the an ultra performance PAO based fully synthetic engine oil designed for use in modified high performance turbo-charged and racing engines. Tested and proven to deliver exceptional performance with outstanding all-season protection. Maximum engine protection even under extreme heat and wear conditions. Optimal wear protection, reduced friction, excellent start-up and high-rpm wear protection offered by its unique additive formulation.

Specifications :

ACEA A3 / B3 / B4; API SN / CF; Fiat 9.55535-H3; VW 501 01 / 505 00; MB 229.3

Typical Properties:

SAE Grade: SAE 10W-60

Test	Method	Unit	Result
Density @ 15°C	ASTM D4052-09	kg / L	0.8503
Kinematic Viscosity @40°C	ASTM D445-10	cSt	171.0
Kinematic Viscosity @100°C	ASTM D445-10	cSt	25.70
Viscosity Index	ASTM D2270-04		185
Flash Point, COC	ASTM D92-05a (10)	°C	245.0
Pour Point	ASTM D97-09	°C	- 18
Base Number	ASTM D2896-07a	mg KOH/g	6.61

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.