

Safety Data Sheet According to 1907/2006/EC, Article 31

Printing Date 25.03.2022 - Revision 25.03.2022

1.Identication of Product and Company's Name:

PRODUCT DETAIL

Trade Name: OWS Ignite SAE 5W-40

Article Number: 3748

Application of the substance / the preparation:

Manufacturer / Supplier:

Our Workshop System (S) Pte Ltd

107 Tuas View Walk 1, Singapore 637730

Tel: +65 6452 3209 Fax: +65 6452 0586 www.ows-asia.com

Further information obtainable from:

Labor: Gordon Chiew Tel: (65) 9818 3860

E-mail: gordon@ows-germany.com

Information in case emergency: Tel: (49) 171 9978 792 Monday to Friday 9:00 to 18:00 CET

2. Possible Hazards:

2.1. Classification of the substance or mixture

This mixture is not classified as dangerous according to Directive 1999/45/EC.

2.2. Label elements

Additional advice on labelling

According to EC directives or the corresponding national regulations there is no labelling obligation for this product.

2.3. Other hazards

No data available

3. Composition/Ingredients:

3.2. Mixture

Component	Synonyms	CAS No.	Content (%)
Distilled, Hydrogenated, Heavy Paraffinic	Hydrotreated (severe) heavy paraffinic distillate	64742-54-7	20-30
Hydrogenated Decene Homopolymer	Saturated Olefin Hydrocarbons	68037-01-4	50-60
Zinc Alkyl Dithiophosphate	Phosphorodithioic Acid	68649-42-3	<1
Polyol Ester	Trimethylolpropane caprylate/capriate	11138-60-8	5-10
Ethylene- Propylene Copolymer	1-Propene, Polymer with Ethene	9010-79-1	1-5

4. First Aid Measures:

4.1. Description of first aid measures General information Self-protection of the first aider.

Change contaminated clothing.

Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

In case of inhalation of aerosols/spray mist/splash spots: Consult physician.

Provide fresh air. Avoid breathing dust/fume/gas/mist/vapours/spray.

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

In case of inhalation of aerosols/spray mist/splash spots: Consult physician.

After contact with skin

After contact with skin, take off immediately all contaminated clothing,

and wash immediately with plenty of water and soap.

If skin irritation or rash occurs: Get medical advice/attention.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink large quantities of water.

If swallowed, do not induce vomiting: seek medical advice immediately and show this container label.

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

Caution if victim vomits: Risk of aspiration!

Aspiration hazard: Immediately get medical attention.

5. Fire Fighting measures:

5.1. Extinguishing media

Suitable extinguishing media

Extinguishing materials should be selected according to the surrounding area. Carbon dioxide (CO2).

Dry extinguishing powder. Foam.

Extinguishing media which must not be used for safety reasons

High power water jet.

5.2. Special hazards arising from the substance or mixture

Special exposure hazards arising from the substance itself, combustion products, resulting gases:

Carbon dioxide (CO2). Carbon monoxide. Sulfur oxides. Phosphorus oxides. Hydrogen sulphide (H2S).

5.3. Advice for firefighters

Carbon black In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use a water spray jet to knock down vapours/gases/mists.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

6. Accidental release measures:

6.1. Personal precautions, protective equipment and emergency procedures

High slip hazard because of leaking or

spilled product. Wear suitable protective clothing .

Wear respiratory protection when in the presence of vapour, dust, and aerosols.

6.2. Environmental precautions

Do not empty into drains or the aquatic environment.

Prevent spreading over great surfaces (e.g. by damming or installing oil booms).

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Treat the assimilated material according to the section on waste

6.4. Reference to other sections

In case of gas being released or leakage into waters, ground or the drainage system, the appropriate authorities must be informed.

7. Storage and Handling:

7.1. Precautions for safe handling

Advice on safe handling

Protect skin by using skin protective cream. Wash hands before breaks and at the end of work .

Conditions to avoid: aerosol or mist generation.

Advice on protection against fire and explosion

No special measures are necessary.

When using do not smoke.

Fire class: B (German Industry Norms (DIN) / European Norms (EN): EN2)

Further information on handling

No data available

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Keep away from heat. Keep/Store only in original container.

Advice on storage compatibility

Do not store together with: Food and fodder, Oxidizing agents.

Further information on storage conditions

If product enters soil, it will be mobile and may contaminate groundwater Keep away from heat.

7.3. Specific end use(s)

Motor oil

8. Explosion Control/Personal Protection:

8.1. Control parameters

Exposure limits (EH40)

8.2. Exposure controls

Occupational exposure controls

No data available

Protective and hygiene measures

When using do not eat, drink or smoke.

Change contaminated clothing.

Wash hands before breaks and at the end of work .

Protect skin by using skin protective cream.

Keep away from food, drink and animal feeding stuffs.

Do not breathe vapour.

Respiratory protection

Wear respiratory protection when in the presence of vapour, dust, and aerosols.

Hand protection

Wear suitable gloves.

Eye protection

In case of fine dispersion/spraying/misting: Wear eye/face protection.

Skin protection

In case of fine dispersion/spraying/misting: Wear protective gloves/protective clothing.

9. Physical & Chemical Characteristics:

9.1. Information on basic physical and chemical properties

Appearance / color Visual		Bright & Clear		
Density @ 15 °C, kg/L	ASTM D4052	0.8470		
Density @ 20 °C, kg/L	ASTM D4052	0.8439		
Density @ 30 °C, kg/L	ASTM D4052	0.8376		
Color	ASTM D1500	<3.0		
Kinematic Viscosity @ 40°C, cSt	ASTM D445	81.52		
Kinematic Viscosity @ 100°C, cSt	ASTM D445	14.34		
Viscosity Index	ASTM D2270	185		
TBN, mg/KOH/g	ASTM D2896	6.5		
Flash Point (COC), °C	ASTM D92	230		
Pour Point, °C	ASTM D97	-45		
CCS, cP	ASTM D5293	5336		
HTHS, cP	ASTM D5481	3.57		
Foaming Sq.I, ml/ml	ASTM D892	10/0		
Foaming Sq.II, ml/ml	ASTM D892	10/0		
Foaming Sq.III, ml/ml	ASTM D892	10/0		

9.2. Other information

none/none

10. Stability & Reactivity Data:

10.1. Reactivity

No data available

10.2. Chemical stability

No thermal decomposition if properly stored / handled /transported.

Onset of decomposition at elevated temperatures (>120°C): (e.g. H2S)

10.3. Possibility of hazardous reactions

possible with strong oxidizing agents.

This product is stable under normal conditions. Hazardous reactions are unlikely.

10.4. Conditions to avoid

Oxidizing agents, strong.. Etchant and acids

10.5. Incompatible materials

Oxidizing agents, strong.

10.6. Hazardous decomposition products

none/none

Further information

No thermal decomposition if properly stored / handled /transported.

11. Toxicological Information:

11.1. Information on toxicological effects

Toxicocinetics, metabolism and distribution

No data available.

Acute toxicity

No data available.

Irritant effect on the respiratory tract: Do not breathe gas/vapour.

CAS No	Chemical name					
	Exposure routes	Method	Dose	Species	Source	
72623-87-1	Baseoil - unspecified, Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based					
	oral	LD50 mg/kg	=> 5000	Rat.	OECD 401	
	dermal	LD50 mg/kg	= > 2000	Rabbit.	OECD 402	
	inhalative (4 h)	LC50 mg/l	= > 5.53	Rat.	OECD 403	
72623-87-1	Baseoil - unspecified, Lubric	ating oils (pe	etroleum), C20-	50, hydrotreated neutral oil-based		
	oral	LD50 mg/kg	=> 5000	Rat.	OECD 401	
	dermal	LD50 mg/kg	= > 2000	Rabbit.	OECD 402	
	inhalative (4 h)	LC50	= > 5.53	Rat.	OECD 403	

mg/l

Specific effects in experiment on an animal

No data available.

Irritation and corrosivity

Irritant effect on the skin: none/none

Frequent and prolonged eye contact may cause eye irritation.

Sensitising effects

Due to the very low concentration of sensitizing substances,

the finished product can be assumed not to be skin-sensitizing.

Severe effects after repeated or prolonged exposure

Frequently or prolonged contact with skin may cause dermal irritation.

Carcinogenic/mutagenic/toxic effects for reproduction

The product is not classified.

Additional information on tests

The classification was undertaken in accordance with the calculation method governed by the Preparations Directive (1999/45/EC).

Empirical data on effects on humans

not applicable

Has degreasing effect on the skin.

Further information

No special hazards known when the product is properly used and the precautionary measures indicated are observed.

12. Ecological Information:

12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS No	Chemical name							
	Aquatic toxicity	Method	Dose	h	Species	Source		
72623-87-1	Baseoil - unspecified, Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based							
	Acute fish toxicity	LC50	> 100 mg/l	96		OECD 203		
	Acute algae toxicity	ErC50	>= 100 mg/l	72		OECD 201		
	Acute crustacea toxicity	EC50 mg/l	> 10 000	48		OECD 202		
72623-87-1	Baseoil - unspecified, Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based							
	Acute fish toxicity	LC50	> 100 mg/l	96		OECD 203		
	Acute algae toxicity	ErC50	>= 100 mg/l	72		OECD 201		
	Acute crustacea toxicity	EC50 mg/l	> 10 000	48		OECD 202		

12.2. Persistence and degradability

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants. It is eliminable from water only with difficulty. Not easily bio-degradable (according to OECD-criteria). Product is partially biodegradable. Significant residues remain. Post-use oils must not be discharged into the sewer system or into surface waters nor must they be allowed to enter the soil.

12.3. Bioaccumulative potential

No data available.

Do not allow uncontrolled leakage of product into the environment.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
72623-87-1	Baseoil - unspecified, Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-	> 6

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available

12.6. Other adverse effects

Aquatic organisms:

No data available. Effects in sewage plants

No data available. No data available.

Further information

Do not empty into drains or the aquatic environment.

The classification was undertaken in accordance with the calculation method governed by the

Preparations Directive (1999/45/EC).

13. Disposal Instructions:

13.1. Waste treatment methods

Advice on disposal

The waste codes stated are recommendations based on the expected use of the substance and may be reassigned to other waste codes by the user, if applicable.

Waste disposal according to official state regulations .

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

Waste disposal number of waste from residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (except edible oils, and those in chapters 05, 12 and 19); waste engine, gear and lubricating oils; synthetic engine, gear and lubricating oils Classified as hazardous waste.

Waste disposal number of used product

130205 OIL WASTES AND WASTES OF LIQUID FUELS (except edible oils, and those in chapters 05, 12 and 19); waste engine, gear and lubricating oils; synthetic engine, gear and lubricating oils Classified as hazardous waste.

Contaminated packaging

Dispose of this material and its container to hazardous or special waste collection point. Cleaned containers may recycled. Handle contaminated packaging in the same way as the substance itself.

14. Transportation Instructions:

Land transport (ADR/RID)

• UN proper shipping name: Motor oil

Other applicable information (land transport)

No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.2. UN proper shipping name: Motor oil

Other applicable information (inland waterways transport)

No dangerous good in sense of this transport regulation.

Marine transport

14.2. UN proper shipping name: Motor oil **Other applicable information (marine transport)**

No dangerous good in sense of this transport regulation.

Air transport

14.2. UN proper shipping name: Motor oil **Other applicable information (air transport)**

No dangerous good in sense of this transport regulation.

15. Regulation Instructions:

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulatory information

Additional information

According to EC directives or the corresponding national regulations there is no labelling obligation for this product.

National regulatory information

Water contaminating class (D):

16. Other Information:

Full text of R-phrases referred to under sections 2 and 3

53 May cause long-term adverse effects in the aquatic environment.

Full text of H-Statements referred to under sections 2 and 3

H304 May be fatal if swallowed and enters airways.

H413 May cause long lasting harmful effects to aquatic life .