



OWS 300 Racing Brake Fluid Dot 4

100% Fully Synthetic High-Performance Racing Brake Fluid with Elevated Dry Boiling Point

Product Description:

100% fully synthetic high-performance brake fluid with elevated dry and wet boiling point, developed for use in racing and other high-stress environments. Enhanced corrosion protection for all hydraulic brake systems. For use in hydraulic clutch systems, according to manufacturer's instructions.

Specifications :

ISO 4925 Class 4; SAE J1703/1704
 Fiat 9.55597; Renault; MAN; Ford; NH 800 A Opel/GM 19 42 421

Typical Properties:

SAE Grade: Dot 4

Test	Method	Unit	Result
Density @ 15°C	ASTM D4052-09	kg/L	1.0749
Kinematic Viscosity @40°C	ASTM D445-10	cSt	9.070
Equilibrium Boiling Point	ASTM D1120-08	°C	264
Water Content	Karl Fischer	wt %	0.232
Flush Point	COC	°C	140
PH	PH Meter		6.7

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.