



OWS 436 Longlife Coolant Concentrate

Product Description:

A premium quality, ethylene glycol based anti-freeze coolant and corrosion inhibitor concentrate, designed primarily to meet the stringent corrosion protection requirements of modern car engines which have significant amount of aluminium in their construction.

Benefits:

- Suitable for cast iron and aluminium engines
- Protects cooling systems from corrosion and deposits
- Provides a higher boiling point for protection against engine overheating
- Prevents coolant freezing
- Maximises aluminium engine component life
- Long Service life
- Non-aggressive on all hoses and seals

Specifications:

In compliance to EEC regulations the quality of OWS 436 Longlife Coolant is according to the following standards / specifications:

- ASTM D3306
- ASTM D4985
- SAE J1034

Mixing Ratios

Frost protection approx.	Parts coolant additive	Parts tap water
-18°C	1	2
-25°C	1	1.5
-37°C	1	1

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.

Typical Properties:

Test	Method	Unit	Value
Density at 20 °C	DIN 51 757	g/ml	1,116
Viscosity at 20 °C	DIN 51 562	mm ² /s	25
Flash point	ISO 2592	°C	>110
Pour point 1:1 CA / water	ISO 3016	°C	approx -37°C
Boiling Point	ASTM D 1120	°C	>170

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.