



OWS Super Leichtlauf SAE 5W-30 HD

HC Fully Synthetic Engine Oil for All Modern Cars

Product Description:

OWS Super Leichtlauf SAE 5W30 HD is a high-performance HC Fully Synthetic engine oil designed for use in modern Japanese and European Engines with tight tolerances. Turbo tested. Excellent Performance and Fuel Economy qualities. Strengthened with OWS Synthetic oil additives to provide superior engine wear protection and heat tolerance compared with regular synthetic oils in the market.

Feature and Benefits:

- Advance cleaning agents reduce engine deposits and sludge build-up for enhance engine life
- Special OWS Synthetic Additive that provides high wear protection with reduced friction
- HC Fully Synthetic technology that enhances thermal and oxidation stability of engine oil

Specifications:

ACEA A3 / B3 / B4; API SN / CF; VW 501 01 / 505 00; MB 229.1

Typical Properties:

SAE Grade: 5W-30

Test	Method	Unit	Result
Density @ 15°C	ASTM D4052-09	kg/L	0.86
Kinematic Viscosity @40°C	ASTM D445-10	cSt	73.55
Kinematic Viscosity @100°C	ASTM D445-10	cSt	12
Viscosity Index	ASTM D2270-04		159.1
Flash Point, COC	ASTM D92-05a (10)	°C	230
Pour Point	ASTM D97-09	°C	-39.2
Base Number	ASTM D2896-07a	mg KOH/g	7

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.