



OVS 500 Series SAE 15W-50

Semi Synthetic engine oil for motorcycles.

Product Description:

OVS 500 Series SAE 15W-50 is a high performance semi synthetic engine oil specially designed for use in 4-stroke motorcycles with work under severe operation conditions and is can be used in gearbox and wet clutches.

OVS 500 Series SAE 15W-50 is based on high quality mineral en synthetics base stocks in combination with a special selected additive package to obtain the following properties.

- Very good thermal- and oxidation stability.
- Excellent anti-wear, anticorrosion and antifoam properties.
- High friction properties to eliminate clutch slippage.
- Low temperature to ensure an easy cold start.

Specifications:

OVS 500 Series SAE 15W-50 exceeds the following performance criteria:

API SL

JASO MA

PROPERTIES	UNIT	METHOD	VALUE
SAE Grade		SAE J300	15W-50
Density @15°C	kg/m3	ASTM D4052	874
Kin. Viscosity @40°C	mm2/s	ASTM D7042	134
Kin. Viscosity @100°C	mm2/s	ASTM D7042	17.3
Viscosity Index		ASTM D2270	147
Viscosity -20°C, max.	cP	ASTM D5293	7000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D97	-33
Total Base Number	mgKOH/g	ASTM D2896	7.7
Sulphated Ash	%Wt	ASTM D874	0.89

Typical properties are typical of those obtained with normal production tolerance and do no constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.