



# Safety Data Sheet According to 1907/2006/EC, Article 31

Printing Date 25.03.2022 - Revision 25.03.2022

## 1. Identification of Product and Company's Name:

### PRODUCT DETAIL

**Trade Name:** OWS 535 Body Flex Gel

**Article Number:** 535

**Application of the substance / the preparation:**

**Manufacturer / Supplier:**

Our Workshop System (S) Pte Ltd  
107 Tuas View Walk 1, Singapore 637730

Tel: +65 6452 3209

Fax: +65 6452 0586

[www.ows-asia.com](http://www.ows-asia.com)

**Further information obtainable from:**

Labor: Gordon Chiew

Tel: (65) 9818 3860

E-mail: [info@ows-asia.com](mailto:info@ows-asia.com)

**Information in case emergency:** Tel: (49) 171 9978 792 Monday to Friday 9:00 to 18:00 CET

## 2. Hazards identification:

**Hazard designation:**



Xn Harmful

**Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Harmful: may cause lung damage if swallowed.

R12 Extremely flammable.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition

– No smoking.

Buildup of explosive mixtures possible without sufficient ventilation.

Keep out of the reach of children

**Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

## 3. Composition/Ingredients:

**Chemical characterization**

**Description:** Mixture of substances listed below with nonhazardous additions.

**Dangerous components:**


CAS: 75-28-5	isobutane	 F+; R12	45%
EINECS: 200-857-2			
CAS: 64742-49-0	Naphtha (petroleum), hydrotreated light		25%

EINECS: 265-151-9

 Xn,  Xi,  F,  N; R 11-38-51/53-65-67

CAS: 74-98-6

propane


 F+; R12

25%

EINECS: 200-827-9

CAS: 106-97-8

butane

 F+; R12

5%

**Additional information:** For the wording of the listed risk phrases refer to section 16.

## 4. First Aid Measures:

### After inhalation:

Supply fresh air; consult doctor in case of complaints.

Take affected persons into fresh air and keep quiet.

### After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Immediately remove any clothing soiled by the product.

### After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

### After swallowing:

Do not induce vomiting; call for medical help immediately.

## 5. Fire Fighting measures:

### Suitable extinguishing agents:

Foam

Fire-extinguishing powder

Carbon dioxide

**For safety reasons unsuitable extinguishing agents:** Water with full jet

### Special hazards caused by the substance, its products of combustion or resulting gases:

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

**Protective equipment:** Wear self-contained respiratory protective device.

### Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

## 6. Accidental release measures:

### Person-related safety precautions:

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

### Measures for environmental protection:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

### Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

### Additional information:

See Section 13 for disposal information.

## 7. Storage and Handling:

### Handling:

### Information for safe handling:

Ensure good ventilation/exhaustion at the workplace.  
Avoid contact with skin and eyes.

**Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights.  
Do not pierce or burn, even after use.  
Do not spray onto a naked flame or any incandescent material.

**Storage:**

**Requirements to be met by storerooms and receptacles:**

Store in a cool location.  
Observe official regulations on storing packagings with pressurized containers.

**Information about storage in one common storage facility:**

Not required.

**Further information about storage conditions:**

Protect from heat and direct sunlight.

## 8. Explosion Control/Personal Protection:

**Additional information about design of technical facilities:** No further data; see item 7.

**Ingredients with limit values that require monitoring at the workplace:**

**106-97-8 butane**

**WEL** Short-term value: 1810 mg/m<sup>3</sup>, 750 ppm  
Long-term value: 1450 mg/m<sup>3</sup>, 600 ppm  
Carc (if more than 0.1% of buta-1.3-diene)

**Additional information:**

The lists valid during the making were used as basis.

**Personal protective equipment:**

**General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes and skin.  
Not required.

**Respiratory protection:**

**Recommended filter device for short term use:**

Filter AX

**Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

**Material of gloves**

Butyl rubber, BR

**Recommended thickness of the material:**

≥ 0.45 mm

**Penetration time of glove material**

≥ 240 min

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye protection:**



Tightly sealed goggles

**Body protection:**

Protective work clothing

## 9. Physical & Chemical Characteristics:

**General Information**

**Form:** Aerosol

**Colour:** Colourless

**Odour:** Petrol-like

**Change in condition**

**Melting point/Melting range**

: Undetermined.

**Boiling point/Boiling range**

: < 0°C.

- **Flash point** : Not applicable, as aerosol.
- **Ignition temperature** : >200°C
- **Danger of explosion** : Product is not explosive. However, formation of explosive air / vapour mixtures are possible.
- **Density at 20°C** : 0.67815 g/cm<sup>3</sup>
- **Solubility in / Miscibility with water** : Not miscible or difficult to mix.
- Organic solvents** : 63.1 %

## 10. Stability & Reactivity Data:

- Thermal decomposition / conditions to be avoided** : No decomposition if used according to specifications.
- Dangerous reactions** : No dangerous reactions known.
- Dangerous decomposition products** : Aldehyde  
Carbon monoxide and carbon dioxide

## 11. Toxicological Information:

### Acute toxicity:

### LD/LC50 values relevant for classification:

<b>64742-49-0</b>	Naphtha (petroleum), hydrotreated light
Oral	LD50 >2000 mg/kg (rat)
Dermal	LD50 >2000 mg/kg (rab)
Inhalative	LC50/4 h >5 mg/l (rat)

### Primary irritant effect:

- on the skin:** Irritant to skin and mucous membranes.
- on the eye:** No irritating effect.
- Sensitization:** No sensitizing effects known.
- Additional toxicological information:**  
Vapours have narcotic effect.

## 12. Ecological Information:

### Ecotoxicological effects:

**Remark:** Harmful to fish

### General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Harmful to aquatic organisms

## 13. Disposal Instructions:

### Product:

#### Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

#### European waste catalogue

- 16 05 04 gases in pressure containers (including halons) containing dangerous substances
- 15 01 04 metallic packaging

#### Uncleaned packaging:

**Recommendation:** Disposal must be made according to official regulations

## 14. Transportation Instructions:

### Land transport ADR/RID (cross-border)



- **ADR/RID class:** 2.1 Flammable Gases.
- **Danger code (Kemler):** -
- **UN-Number:** 1950
- **Packaging group:** -
- **Hazard label:** 2.1
- **Description of goods:** 1950 AEROSOLS

### · Maritime transport IMDG:



- **IMDG Class:** 2.1
- **UN Number:** 1950
- **Label:** 2.1
- **Packaging group:** -
- **EMS Number:** F-D,S-U
- **Marine pollutant:** No
- **Proper shipping name:** AEROSOLS

### · Air transport ICAO-TI and IATA-DGR:



- **ICAO/IATA Class:** 2.1
- **UN/ID Number:** 1950
- **Label:** 2.1
- **Packaging group:** -
- **Proper shipping name:** AEROSOLS, flammable

## 15. Regulation Instructions:

### Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

### Code letter and hazard designation of product:



F+ Extremely flammable,

### Risk phrases:

12 Extremely flammable.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

66 Repeated exposure may cause skin dryness or cracking.

67 Vapours may cause drowsiness and dizziness.

### Safety phrases:

23 Do not breathe aerosol.

29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

46 If swallowed, seek medical advice immediately and show this container or label.

51 Use only in well-ventilated areas.

**Special labelling of certain preparations:**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Keep away from sources of ignition – No smoking.

Buildup of explosive mixtures possible without sufficient ventilation.

Keep out of the reach of children

**16. Other Information:**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Relevant R-phrases**

11 Highly flammable.

12 Extremely flammable.

38 Irritating to skin.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

67 Vapours may cause drowsiness and dizziness.

\* **Data compared to the previous version altered.**