



# OVS 600 Syntholite SAE 15W-50

Fully Synthetic 4 cycle oil developed for all High Performance motorcycle engines.

## Product Description:

OVS 600 Series SAE 15W-50 is a fully synthetic 4T engine oil blended with advance additives. Provides a good and economical solution for high performance and engine protection. OVS 600 Series Syntholite SAE 15W-50 provides optimum engine protection, reduced friction and lower operation temperatures. It ensures engine cleanliness and smooth gear changes.

## Feature and Benefits:

- Anti-wear for valvetrain protection
- Exceeds JASO-MA 2 specifications
- Reduced friction and engine oil temperature
- Viscosity stability under extreme conditions
- Reduced engine wear

## Specifications :

JASO-MA 2

## Typical Properties:

SAE Grade: **15W-50**

Test	Method	Unit	Result
Density @ 15°C	ASTM D4052-09	kg / L	0.8757
Kinematic Viscosity @40°C	ASTM D445-10	cSt	108.0
Kinematic Viscosity @100°C	ASTM D445-10	cSt	14.30
Viscosity Index	ASTM D2270-04		135
Flash Point, COC	ASTM D92-05a (10)	°C	239.0
Pour Point	ASTM D97-09	°C	-42
Base Number	ASTM D2896-07a	mg KOH/g	10.04

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.