TECHNICAL DATA SHEET



OWS Syntho Ultimate SAE 10W-50

Street Performance 4 cycle oil developed for high HP and High RPM Street and Performance bikes

Product Description:

OWS SYNTHO ULTIMATE 10W50 is a fully synthetic Street-Performance 4T engine oil. Increases engine performance, eases cold starts, prolongs oil life and decreases sludge while neutralising corrosives formed in the oil. High detergency content ensures engine cleanliness and prevents varnish and carbon deposits. Designed for bikes with wet clutch, providing smooth gear engagement.

Feature and Benefits:

- Anti-wear for valvetrain protection
- Exceeds API SN & JASO-MA 4T specifications
- · Reduced friction and engine oil temperature
- Viscosity stability under extreme conditions
- Reduced engine wear

Specifications :

SN & JASO-MA 4T

Typical Properties:

SAE Grade:

10W50

Test	Method	Unit	Result
Density @ 15°C	ASTM D4052-09	kg/L	0.8634
Kinematic Viscosity @40°C	ASTM D445-10	cSt	138.5
Kinematic Viscosity @100°C	ASTM D445-10	cSt	19.20
Viscosity Index	ASTM D2270-04		158
Flash Point, COC	ASTM D92-05a (10)	C°	>220
Pour Point	ASTM D97-09	C°	-36
Base Number	ASTM D2896-07a	mg KOH/g	8.0

Typical properties are typical of those obtained with normal production tolerance and do no constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.