



OWS 800 Syntholite SAE 10W-40

Racing Spec 4 cycle oil developed for High HP & High RPM Street and Performance Bikes

Product Description:

OWS 800 Syntholite is a Fully Synthetic 4T engine oil blended with advance additives. Provides a good and cost-effective all around solution to all 4 cycle engines. OWS 800 Series Syntholube SAE 10W-40 provides maximum engine protection, reduced friction and lower operating temperatures and ensures engine cleanliness and smoother gear changes.

Feature and Benefits:

- Anti-wear for valvetrain protection
- Exceeds JASO-MA 2 specifications
- Reduced friction and engine oil temperature
- Viscosity stability under extreme conditions
- Reduced engine wear

Specifications :

JASO-MA 2

Typical Properties:

SAE Grade: **10W-40**

Test	Method	Unit	Result
Density @ 15°C	ASTM D4052-09	kg / L	0.8648
Kinematic Viscosity @40°C	ASTM D445-10	cSt	101.2
Kinematic Viscosity @100°C	ASTM D445-10	cSt	14.5
Viscosity Index	ASTM D2270-04		148
Flash Point, COC	ASTM D92-05a (10)	°C	>220
Pour Point	ASTM D97-09	°C	-32
Base Number	ASTM D2896-07a	mg KOH/g	7.5

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.