TECHNICAL DATA SHEET



OWS ATF Dexron III H

Multi-Functional Universal Automatic Transmission Fluid

Product Description:

OWS ATF Dexron III H is a synthetic based Automatic Transmission Fluid (ATF) specially developed for a broad usage spectrum in automatic transmissions, power steering units and hydraulic drives.

OWS ATF Dexron III H is manufactured using the highest quality Synthetic base stocks and state of the art Überclean® additive technology. This ensures a finished product with an unmatched performance level.

OWS ATF Dexron III H fulfils or exceeds the following specifications:

Dexron III H

MB 236.1 / 236.6 / 236.9 / 236.10

ZF TE-ML 04D, 05L, 14B/C, 16L, 17C

VOITH H 55.6336.3X

Volvo Transmission Oil 97341, VOLVO 1161521 / 1161621

Allison C-4

BMW LA-2634 / LT-71141 / ETL 7045 E

Ford M2C195-A / M2C202-B / M2C922-A1

GM 9986195

Hyundai / Kia / Mitsubishi SP-II/-III

MAN339TypeV1/V2/Z2/Z3

Test	Method	Unit	Result
Density @ 15°C	ASTM D4052	kg/L	0.850
Kinematic Viscosity @40°C	ASTM D445	cSt	36.8
Kinematic Viscosity @100°C	ASTM D445	cSt	7.3
Viscosity Index	ASTM D2270		168
Flash Point, COC	ASTM D92-05A	°C	> 210
Pour Point	ASTM D97	°C	<-45

Typical properties are typical of those obtained with normal production tolerance and do no constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.