

Safety Data Sheet According to 1907/2006/EC, Article 31

Printing Date 25.03.2022 - Revision 25.03.2022

1.Identication of Product and Company's Name:

PRODUCT DETAIL Trade Name: OWS Multi-Vehicle ATF Article Number: 8120 Application of the substance / the preparation: Manufacturer / Supplier: Our Workshop System (S) Pte Ltd 107 Tuas View Walk 1, Singapore 637730 Tel: +65 6452 3209 Fax: +65 6452 0586 www.ows-asia.com Further information obtainable from:

Labor: Gordon Chiew Tel: (65) 9818 3860 E-mail: *gordon@ows-germany.com* Information in case emergency: Tel: (49) 171 9978 792 Monday to Friday 9:00 to 18:00 CET

2. Possible Hazards:

Hazard designation:

The product does not require a hazard warning label in accordance with EC directives/ GefStoffV (German regulations on dangerous substances).

3. Composition/Ingredients:

3.2. Mixtures

Hazardous ingredients

CAS No.	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
64742-54-7	Destillates (petroleum), hydrotreated heavy paraffinic			34 - 43%
64742-55-8	Destillate (Erdöl), mit Wasserstoff behandelte leichte paraffinhaltige; Grundöl - nicht spezifiziert		50 - < 55 %	
	265-158-7	649-468-00-3	01-2119487077-29	
	Asp. Tox. 1; H304			
398141-87-2	Thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11-isoalkyloxy) derivs., C10-rich		1- < 5%	
	800-172-4		01-2119969520-35	
	Aquatic Chronic 2; H411			
	Amines, dicoco alkyl, reaction prods with hydroxyacetic acid. [EC-No.: 471-920-1]			<1 %
	471-920-1		01-0000019770-68	
	Skin Sens. 1B; H317			
	1,2-Propanediol, 3-amino-, N,N-dicoco alkyl derivs. [EC-No.: 482-000-4]			<1 %
	482-000-4		01-000020142-86	
	Skin Sens. 1B, Aquatic Chronic 3; H317 H412			
67124-09-8	1-(tert-dodecylthio)propan-2-ol			<1 %
	266-582-5		01-2119953277-30	
	Skin Sens. 1B, Aquatic Acute 1, Aquatic Chronic 1; H317 H400 H410			
122-39-4	diphenylamine		<1 %	
	204-539-4	612-026-00-5		
	Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, Eye Irrit. 2, STOT RE 2, Aquatic Acute 1,			
	Aquatic Chronic 1; H331 H311 H301 H319 H373 H400 H410			

75975-85-8	Benzene, polypropene derivatives, sulfonated, calcium salts		
	Skin Sens. 1B; H317		
1471314-23-4	C14-18 alpha-olefin epoxide, reaction products with boric acid		<1 %
	939-580-3	01-2119976364-28	
	Skin Sens. 1B; H317		
1218787-32-6	2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol		< 0.1 %
	620-540-6	01-2119510877-33	
	Acute Tox. 4, Skin Corr. 1C, Eye Dam. 1, Aquatic Acute 1 (M-Factor = 10),		
	Aquatic Chronic 2; H302 H314 H318 H400 H411		
95-38-5	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol		< 0.1 %
	202-414-9	01-2119777867-13	
	Acute Tox. 4, Skin Corr. 1C, Eye Dam. 1, STOT RE 2, Aquatic Acute 1 (M-Factor = 10),		
	Aquatic Chronic 1 (M-Factor = 1); H302 H314 H318 H373 H400 H410		

Other information

Note L : The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method', Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

4. First Aid Measures:

General information

Remove contaminated clothing immediately and dispose of safely.

After skin contact

In case of contact with skin wash off immediately with plenty of

After eye contact

In case of contact with the eyes, rinse thoroughly with plenty of water or with an eye-cleaning solution. In case of irritation consult an oculist.

After ingestion

Do not induce vomiting.

Rinse out mouth and give plenty of water to drink. Summon a doctor immediately.

5. Fire Fighting Measures

Suitable extinguishing media: Foam, Dry powder, Carbon dioxide **Extinguishing media that must not be used for safety reasons:** Full water jet **Special exposure hazards arising from the substance or preparation**

itself, its combustion products or from resulting gases

In the event of fire the following can be released:

- -- Carbon monoxide (CO), Carbon dioxide (CO2)
- In case of combustion evolution of dangerous gases possible: -- SO2, H2S

Special protective equipment for firefighting

Do not inhale explosion and/or combustion gases.

Use self-contained breathing apparatus.

Other information

Cool endangered containers with water spray jet.

6. Accidental Release Measures:

Personal precautions Use personal protective clothing. Environmental precautions Do not discharge into the drains/surface waters/groundwater. Methods for cleaning up/taking up Take up with absorbent material (eg sand, kieselguhr, universal binder). Dispose of absorbed material in accordance with the regulations.

7. Storage and Handling:

Handling

Advice on safe handling Use personal protective clothing. Open and handle container with care. Avoid formation of aerosols. Advice on protection against fire and explosion No special measures necessary.

Storage

Requirements for storage rooms and vessels Protect from frost. Protect from heat and direct sunlight. Keep container tightly closed.

8. Explosion Control/Personal Protection:

Additional hints on technical system design.

See chapter 7; no measures exceeding the ones mentioned are necessary. Ingredients with occupational exposure limits to be monitored

EINECS-No. Name Type Value Unit

Personal protective equipment

Respiratory protection

Breathing apparatus in the event of aerosol or mist formation.

Hand protection

Recommendation: Impermeable safety gloves made of nitrile as per EN 374; penetration time more than 480 min. at a thickness of 0.4 mm.

Eye protection Safety glasses with side protection shield **General protective measures** Do not inhale gases/vapors/aerosols. Avoid contact with eyes and skin. At work do not eat, drink, smoke or take drugs. Keep away from foodstuffs and beverages. Wash hands before breaks and after work.

9. Physical & Chemical Characteristics:

Test	Method	Unit	Result
Density @ 15°C	ASTM D4052	kg/L	0.843
Kinematic Viscosity @40°C	ASTM D445	cSt	37.4
Kinematic Viscosity @100°C	ASTM D445	cSt	7.0
Viscosity Index	ASTM D2270		150
Flash Point, COC	ASTM D92-05A	°C	230
Pour Point	ASTM D9	°C	-42

10. Stability & Reactivity Data:

Materials to avoid

Reactions with strong oxidising agents.

Hazardous decomposition products.

No hazardous reactions when stored and handled according to prescribed instructions.

11. Toxicological Information:

General remarks

No toxicological data are available.

Experience in practice

Keeping to the general worker's protection rules and the industrial hygienic, there is no risk in handling this product through the personnel.

12. Ecological Information:

Do not discharge into the drains/surface waters/groundwater. The formulation was evaluated using the conventional method of the Dangerous Preparations Directive 1999/45/EC and not classified as hazardous to the environment.

13. Disposal Instructions:

Waste code 130205 -- mineral-based non-chlorinated engine, gear and lubricating oils

The listed waste code numbers, according to the European Waste

Catalogue (EWC), are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company.

Unclean packaging

Uncontaminated packaging may be taken for recycling.

Packaging that cannot be cleaned should be disposed off in agreement with the regional waste disposal company.

14. Transportation Instructions:

"Product is not subject to the regulations for dangerous goods".

15. Regulation Instructions:

Labeling in accordance with EC directives

The product does not require a hazard warning label in accordance with EC directives/ GefStoffV (German regulations on dangerous substances).

National regulations

Water hazard class / source: 2 TA-Luft / paragraph (for Germany only): Class III VbF (Germany) : -

16. Other Information:

n.a.

The data mentioned in the present safety data sheet correspond to our latest knowledge and experience and may be used to precise safety requirements for the different products. The information given therein is no warranty as to quality.

Revised chapters: 1,2,3,8,11,12,16.

n.a.: not applicable n.b.: not determined