TECHNICAL DATA SHEET



OWS 900 Synthomax Xtreme SAE 5W60

Racing Spec 4 cycle oil developed for high HP & High RPM Racing & Performance Bikes.

Product Description:

900 SYNTHOMAX XTREME 5W60 is a high performance racing, fully synthetic 4T engine oil. It is specially formulated using the highest quality synthetic base oil and blended with OWS proprietary addictives mixed to deliver the best in high-stress and temperature engine protection for high rpm and racing engines. Specially designed for road bikes with wet clutch, providing smoothest gear engagement.

Feature and Benefits:

- Anti-wear for valvetrain protection
- Exceeds API SN & JASO-MA 2 specifications
- Reduced friction and engine oil temperature
- Viscosity stability under extreme conditions
- Reduced engine wear

Specifications:

API SN & JASO-MA 2

Typical Properties:

SAE Grade: 5W60

Test	Method	Unit	Result
Density @ 15°C	ASTM D4052-09	kg / L	0.8477
Kinematic Viscosity @40°C	ASTM D445-10	cSt	140.0
Kinematic Viscosity @100°C	ASTM D445-10	cSt	21.70
Viscosity Index	ASTM D2270-04		182
Flash Point, COC	ASTM D92-05a (10)	°C	219.0
Pour Point	ASTM D97-09	°C	-51
Base Number	ASTM D2896-07a	mg KOH/g	7.43

Typical properties are typical of those obtained with normal production tolerance and do no constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.