

# OWS Additized Petrol P282

(FOR PETROL ENGINES)

## Product Description:

OWS Additized Petrol P282 additive protects injectors and intake valves, Improves fuel economy and reduces exhaust emissions. It provides protection against corrosion and emulsion in wet fuel systems.

This unique petrol additive enhances performance and improves combustion delivering fuel saving benefits up to 10%.

Improves combustion efficiency of gasoline engines and reduces wear coefficient along metal-to-metal surfaces.

## Benefits:

- Real Life Fuel Economy
- Cleaner Engine
- Corrosion Control
- Reduced Engine Wear
- Enhanced Combustion
- Less Harmful Emissions

## Application:

- Shake well before use.
- Add product into fuel tank.
- Per can 300 ml is appropriate for 60L fuel for maximum performance

## Handling:

Please refer to the Safety Data Sheet for safety, handling, and toxicity information.

Shelf life: 24 months from date of manufacture if stored in original sealed containers in a sheltered environment.

## Storage:

Store the product in a dry, well-ventilated place, preferably without direct exposure to sunlight. Do not store the product with food and drink.

## Characteristics

Appearance	Amber Liquid	Kinematic Viscosity @ 40 °C, cSt	10 max.
Density @ 15°C, kg/l	0.875 – 0.915	Kinematic Viscosity @ 20 °C, cSt	15 max.
Flash Point, °C	62 min.	Max. Handling Temperature	Ambient Temperature

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.