ADJUSTABLE PEDESTAL 8/20 MM

PAVING





Adjustable pedestal 8/20 mm

The adjustable slab pedestal from 8 to 20 mm allows the installation of terrace of low height. It can be adjusted from 8 to 15 mm without the wedge or up to 20 mm with. It is ideal for creating a roof top or covering an existing



Note: Always calculate the height you want to catch up by deducting the thickness of the coating in order to obtain the necessary pedestal size.



Application & use

Creation of terraces in porcelain stoneware, stone, concrete or gratings for pedestrian use.

The installation on pedestals requires the use of a covering with a minimum thickness of 2cm. It is possible to use tiles (porcelain stoneware), concrete slabs, reconstituted stone or rectified natural stone (5cm thick).

Technical Characteristics

Composition: polypropylene (recycled and recyclable)

Color: black

Origine: France

Garantee: 10 years

Conformity: norm DTU 43.1

Use: pedestrian only

Base diameter: 170 mm

Head diameter: 125 mm

Lugs dimension: height 12 mm / thickness 3 mm

Resistance to temperatures: from -40°C to +60°C

Resistance to atmospheric agents: UV and freeze

Load resistance: up to 1 ton

Product Advantages

- + Simplified ground preparation
- + Base designed to ensure proper drainage of stormwater
- + Quick and convenient installation without glue or joint
- Compatible with many slab coatings
- Adjustment to the millimeter thanks to the nut without additional tools
- + Removable lugs for a smooth head (for edging)
- + Compatible accessory: vibration buffers

