

Safety Data Sheet

Fortis 3D Corp. SDS Revision date: November 16, 2021

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: FORTIS3D™ Filaments: FF5040

Recommended Use: 3D printing/additive manufacturing via filament extrusion

Uses Recommended Against: Grinding, Burning
Manufacturer: Fortis 3D Corp.
565 Greenwich Street

Brantford, Ontario N3T 5M2

Telephone: +1-833-296-1500 Emergency Phone Number: +1-833-296-1500

SECTION 2. HAZARDS IDENTIFICATION

Hazard Classification

Physical Hazards

Combustible dust, Category 1.

Label Elements

Signal Word: Warning!

Hazard Statements: If dust is formed during handling or processing, May form combustible

concentrations in air

Precautionary P260 – Do not breathe dust

Statements: P285 – In case of inadequate ventilation wear respiratory protection

P501 – Dispose of contents/containers in accordance with local regulations

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Chemical Name	CAS No.	Concentration
Polylactic acid*	Polylactic acid	6100-51-6	>55%

^{*}Classified as non-hazardous. Disclosed to indicate major component.

Composition Comments: There are no other ingredients present which, within the current

knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require

reporting in this section

SECTION 4. FIRST AID MEASURES

General advice If irritation or other symptoms occur or persist from any route of exposure,

remove the affected individual from the area: see a physician/get medical

attention.

If large amounts of vapors released during processing are inhaled, remove

victim to fresh air. If victim is not breathing, provide artificial respiration, preferably mouth to mouth. If victim has difficulty breathing, provide oxygen

and call a physician.

In case of skin contact If molten polymer gets on skin, cool rapidly with cold water. Do not attempt

to peel polymer from skin. Obtain medical treatment for thermal burn.

In case of eye contact Hold eyelids apart and flush eyes with plenty of water for at least 15

minutes. Have eyes examined and tested by medical personnel.

If swallowed Adverse health effects due to ingestion are not anticipated.

Symptoms Thermal burns. Respiratory irritation. Mechanical irritation.

Treatment After adequate first aid, no further treatment is required unless symptoms

reappear. Burns should be treated as thermal burns. Molten resin will come off as healing occurs; therefore, immediate removal from the skin is

not necessary.

SECTION 5. FIRE FIGHTING MEASURES

Fire Fighting Measures: Standard procedure for chemical fires.

Suitable Extinguishing Media: Water spray, dry powder, foam, carbon dioxide.

Fire Fighting Equipment: Wear self-contained breathing apparatus and protective suit. Keep upwind, and evacuate surrounding area. Fight fire from

maximum distance.

Specific hazards arising from the

chemical:

Burning may emit various oligomers, waxes and oxygenated hydrocarbons as well as carbon dioxide, carbon monoxide and small amounts of other organic vapours. Powdered material

may form explosive dust-air mixtures.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal protective equipment and precautions:	Do not handle molten materials bare-handed. Use heat- protective gloves if required.
Cleanup Instructions:	Sweep up and shovel into suitable containers for disposal. Use non sparking metal tools and natural bristle broom. Avoid allowing spilled material to get wet or using water to clean up spillages or residues, unless the quantity remaining is very small.
Environmental precautions:	Material should not be released into the environment.

SECTION 7. HANDLING AND STORAGE

Handling: Do not handle molten materials bare-handed. Use heat-protective gloves if

handling hot materials is required. Avoid eye, skin, and clothing contact. Do not

inhale. Do not taste or swallow. Use only with adequate ventilation. After

handling, wash hand thoroughly with soap and water.

To minimize dust explosion hazards, do not grind the material. If generating dust, ensure adequate ventilation and avoid dust accumulation in air or on surfaces, and prevent buildup of static.

Storage: Keep containers tightly closed in a cool and well-ventilated place.

Dust Explosion Risk

Class 1 (Kst-value <200 bar·m/s) (St 1).

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Dust (Total)	OSHA
	TWA: 15 mg/m ³ .

Personal Protective Equipment

Eye/Face Protection: Wear safety glasses or goggles to protect against dust particles.

Skin Protection: Wear chemical resistant gloves and protective clothing.

Respiratory Protection: Use NIOSH approved respirator as needed to mitigate exposure.

Engineering Controls: Ensure good ventilation in area of work.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Form: Pellets

Color: Various, depending on subgrade

Odor: Not available Odor threshold: Not available Not applicable :Ha Freezing/Melting Point: 170-240 °C **Boiling Point:** Not applicable Flash point: Not applicable **Evaporation Rate:** Not applicable **Vapor Density:** Not applicable **Vapor Pressure:** Not applicable **Specific Gravity:** Not available Solubility in water: Not available Partition Coefficient (Octanol/Water): Not available **Autoignition Temperature:** Not available **Decomposition Temperature:** Not available **Viscosity:** Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity: Under normal conditions of storage and use, hazardous

reactions will not occur

Chemical Stability: Stable under recommended storage conditions. **Conditions to Avoid:** Avoid static discharge. Avoid contact with strong

oxidizers, excessive heat, sparks or open flame.

Hazardous Decomposition Products: No decomposition expected under normal storage

conditions.

Possibility of Hazardous Reactions:

None expected

Incompatible Materials

Strong acids, strong bases, oxidizing agents, fluorine

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Ingestion:	Ingestion of this product is not a likely route of exposure
Inhalation:	During processing, thermal funmes and inhalation of fine
	particles may cause respiratory irritation.
Skin Contact:	During processing, contact with powder or fines may
	cause mechanical irritation. Molten material will produce
	thermal burns.
Eye contact:	During processing, contact with powder or fines may
	cause mechanical irritation. Molten material will produce
	thermal burns.

Symptoms related to the physical, chemical, and toxicological characteristics

- y - p - c - c - c - c - c - c - c - c - c	
Ingestion:	No adverse effects due to ingestion are expected
Inhalation:	Respiratory irritation
Skin Contact:	Mechanical irritation. Thermal burns.
Eye contact:	Mechanical irritation. Thermal burns. May cause mild,
	short-lasting discomfort to the eyes.

Acute toxicity

Oral: LD: >5000 mg/kg (estimated)

Dermal: Not classified **Inhalation:** Not classified

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity:	Based on data available for the component substances,
	the mixture does not meet the criteria for classification.
Persistence and degradability:	Insufficient data for classification. Some component
	substances are known to be non-biodegradable.
Bioaccumulative potential:	No data available.
Mobility in soil:	No data available.
Other adverse effects:	No data available.

SECTION 13. DISPOSAL CONSIDERATIONS

Dispose in accordance with local, state, provincial and federal regulations.

SECTION 14. TRANSPORT INFORMATION

Not regulated for transport.

SECTION 15. REGULATORY INFORMATION

TSCA: On or in compliance with the inventory

DSL: On or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Revision Date: 2021/11/16

Contact Information - Safety, Regulatory and Environmental: +1-833-296-1500

Disclaimer: The information contained herein is based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to such data or information. The user is responsible for determining whether the product is suitable for its intended conditions of use.