

# Safety data sheet

Page: 1/11

BASF Safety data sheet according to UN GHS 4th rev.

Date / Revised: 22.11.2019 Version: 1.0

Product: Ultrafuse® ABS nat.-acrylonitrile butadiene styrene filament

(ID no. 11120801/SDS\_GEN\_00/EN)

Date of print 19.03.2021

#### 1. Identification

#### **Product identifier**

# Ultrafuse® ABS nat.-acrylonitrile butadiene styrene filament

Recommended use: 3D Printing, for industrial use only

# Details of the supplier of the safety data sheet

Company:
BASF 3D Printing Solutions B.V.
Eerste Bokslootweg 17
7821 AT Emmen, Netherlands

Telephone: + 31 591 820 389

E-mail address: sales@basf-3dps.com

# **Emergency telephone number**

International emergency number: Telephone: +49 180 2273-112

# 2. Hazards Identification

#### Classification of the substance or mixture

According to UN GHS criteria

No need for classification according to GHS criteria for this product.

#### Label elements

Globally Harmonized System (GHS)

Date / Revised: 22.11.2019 Version: 1.0

Product: Ultrafuse® ABS nat.-acrylonitrile butadiene styrene filament

(ID no. 11120801/SDS\_GEN\_00/EN)

Date of print 19.03.2021

The product does not require a hazard warning label in accordance with GHS criteria.

#### Other hazards

#### According to UN GHS criteria

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

# 3. Composition/Information on Ingredients

#### **Substances**

Not applicable

#### **Mixtures**

Chemical nature

Polymer

<u>Hazardous ingredients (GHS)</u> According to UN GHS criteria

No particular hazards known.

#### 4. First-Aid Measures

## **Description of first aid measures**

Remove contaminated clothing.

# If inhaled:

Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. If symptoms persist, seek medical advice.

#### On skin contact:

Wash thoroughly with soap and water. Burns caused by molten material require hospital treatment. If irritation develops, seek medical attention.

#### On contact with eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. If irritation develops, seek medical attention.

# On ingestion:

Rinse mouth and then drink 200-300 ml of water. Do not induce vomiting. Seek medical attention.

Date / Revised: 22.11.2019 Version: 1.0

Product: Ultrafuse® ABS nat.-acrylonitrile butadiene styrene filament

(ID no. 11120801/SDS\_GEN\_00/EN)

Date of print 19.03.2021

# Most important symptoms and effects, both acute and delayed

Symptoms: (Further) symptoms and / or effects are not known so far

Hazards: No hazard is expected under intended use and appropriate handling.

#### Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

# 5. Fire-Fighting Measures

# **Extinguishing media**

Suitable extinguishing media: water spray, foam, dry powder

## Special hazards arising from the substance or mixture

Acrylonitrile, Styrene, fumes/smoke, carbon oxides, nitrogen oxides

Traces of the substances/groups of substances mentioned can be released in case of fire or upon excessive heat.

# Advice for fire-fighters

Special protective equipment:

Wear a self-contained breathing apparatus.

Further information:

Dusty conditions may ignite explosively in the presence of an ignition source causing flash fire.

#### 6. Accidental Release Measures

Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Avoid the formation and build-up of dust - danger of dust explosion. Dust in sufficient concentration can result in an explosive mixture in air. Handle to minimize dusting and eliminate open flame and other sources of ignition.

## Personal precautions, protective equipment and emergency procedures

No special precautions necessary.

#### **Environmental precautions**

Do not allow to enter soil, waterways or waste water channels.

# Methods and material for containment and cleaning up

For small amounts: Sweep/shovel up.

For large amounts: Sweep/shovel up. Vacuum up spilled product.

Reclaim for processing if possible. Ensure adequate ventilation. Avoid raising dust. After decontamination, spill area can be washed with water.

Date / Revised: 22.11.2019 Version: 1.0

Product: Ultrafuse® ABS nat.-acrylonitrile butadiene styrene filament

(ID no. 11120801/SDS\_GEN\_00/EN)

Date of print 19.03.2021

# 7. Handling and Storage

# Precautions for safe handling

Avoid inhalation of dusts/mists/vapours. Ensure adequate ventilation. Provide suitable exhaust ventilation at drying process and in the surrounding of processing machines. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Avoid the formation and deposition of dust.

#### Protection against fire and explosion:

Avoid dust formation. Dust in sufficient concentration can result in an explosive mixture in air. Handle to minimize dusting and eliminate open flame and other sources of ignition. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces.

# Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Keep container tightly closed. Avoid extreme heat. Avoid all sources of ignition: heat, sparks, open flame.

Storage stability:

Avoid prolonged storage.

# 8. Exposure Controls/Personal Protection

# **Control parameters**

Components with occupational exposure limits

100-42-5: Styrene 107-13-1: Acrylonitrile

#### **Exposure controls**

#### Personal protective equipment

#### Respiratory protection:

Breathing protection if breathable aerosols/dust are formed. Wear respiratory protection if ventilation is inadequate. Particle filter with medium efficiency for solid and liquid particles (e.g. EN 143 or 149, Type P2 or FFP2)

Hand protection:

Wear chemical resistant protective gloves.

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

Standard work clothes and shoes.

#### General safety and hygiene measures

Wear protective clothing to prevent contact during mechanical processing and/or hot melt conditions. After use of gloves apply skin-cleaning agents and skin cosmetics.

Date / Revised: 22.11.2019 Version: 1.0

Product: Ultrafuse® ABS nat.-acrylonitrile butadiene styrene filament

(ID no. 11120801/SDS\_GEN\_00/EN)

Date of print 19.03.2021

# 9. Physical and Chemical Properties

# Information on basic physical and chemical properties

Form: filament
Colour: white
Odour: odourless

Odour threshold:

not applicable, odour not perceivable

pH value:

not determined

Melting point:

not determined

Boiling point:

not applicable

Flash point:

not applicable

Evaporation rate:

The product is a non-volatile solid.

Flammability: not flammable

Lower explosion limit:

For solids not relevant for classification and labelling.

Upper explosion limit:

For solids not relevant for classification and labelling.

Ignition temperature:

not determined

Vapour pressure:

not applicable

Relative density: 1,05 - 1,07

(25 °C)

Relative vapour density (air):

not applicable

Solubility in water: negligible

Partitioning coefficient n-octanol/water (log Kow):

not applicable for mixtures

Self ignition: not self-igniting

Thermal decomposition: > 300 °C

Viscosity, dynamic:

not applicable, the product is a solid

Viscosity, kinematic:

not applicable, the product is a solid

Fire promoting properties: not fire-propagating

## Other information

Date / Revised: 22.11.2019 Version: 1.0

Product: Ultrafuse® ABS nat.-acrylonitrile butadiene styrene filament

(ID no. 11120801/SDS\_GEN\_00/EN)

Date of print 19.03.2021

Self heating ability: It is not a substance capable of

spontaneous heating.

Radioactivity:

not radioactive for transport

purposes

# 10. Stability and Reactivity

# Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals: No corrosive effect on metal.

# **Chemical stability**

Stable under normal conditions.

# Possibility of hazardous reactions

The product is stable if stored and handled as prescribed/indicated.

#### **Conditions to avoid**

Temperature: > 300 °C

Prolonged exposure to elevated temperatures may result in exothermic decomposition accompanied by a pressure build-up in sealed containers. Avoid all sources of ignition: heat, sparks, open flame.

#### Incompatible materials

Substances to avoid: oxidizing agents

# **Hazardous decomposition products**

Hazardous decomposition products:

Acrylonitrile, Styrene

monomers, gases/vapours, oxides, hydrocarbons

# 11. Toxicological Information

# Information on toxicological effects

#### Acute toxicity

Assessment of acute toxicity:

Contact with molten product may cause thermal burns. Virtually nontoxic after a single skin contact. Virtually nontoxic by inhalation. Virtually nontoxic after a single ingestion. The product has not been tested. The statement has been derived from the properties of the individual components.

#### Irritation

Date / Revised: 22.11.2019 Version: 1.0

Product: Ultrafuse® ABS nat.-acrylonitrile butadiene styrene filament

(ID no. 11120801/SDS\_GEN\_00/EN)

Date of print 19.03.2021

#### Assessment of irritating effects:

May cause slight irritation to the skin. May cause slight irritation to the eyes. May cause slight irritation to the respiratory tract.

# Respiratory/Skin sensitization

#### Assessment of sensitization:

A sensitizing effect on particularly sensitive individuals cannot be excluded.

#### Germ cell mutagenicity

Assessment of mutagenicity: Not classified, due to lack of data.

# Carcinogenicity

Assessment of carcinogenicity: Not classified, due to lack of data.

#### Reproductive toxicity

Assessment of reproduction toxicity: Not classified, due to lack of data.

#### Developmental toxicity

Assessment of teratogenicity: Not classified, due to lack of data.

# Specific target organ toxicity (single exposure)

#### Assessment of STOT single:

Based on available Data, the classification criteria are not met.

# Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

# Assessment of repeated dose toxicity:

The information available on the product provides no indication of toxicity on target organs after repeated exposure.

# **Aspiration hazard**

No aspiration hazard expected.

Date / Revised: 22.11.2019 Version: 1.0

Product: Ultrafuse® ABS nat.-acrylonitrile butadiene styrene filament

(ID no. 11120801/SDS\_GEN\_00/EN)

Date of print 19.03.2021

# 12. Ecological Information

## **Toxicity**

Assessment of aquatic toxicity:

The product has not been tested. The statement has been derived from the structure of the product.

There is a high probability that the product is not acutely harmful to aquatic organisms.

# Persistence and degradability

Assessment biodegradation and elimination (H2O):

Experience shows this product to be inert and non-degradable.

# **Bioaccumulative potential**

Bioaccumulation potential:

The product will not be readily bioavailable due to its consistency and insolubility in water.

# Mobility in soil

Assessment transport between environmental compartments:

Adsorption in soil: Adsorption to solid soil phase is possible.

#### Results of PBT and vPvB assessment

The product does not fulfill the criteria for PBT (Persistent/bioaccumulative/toxic) and vPvB (very persistent/very bioaccumulative).

#### Other adverse effects

No data available.

#### **Additional information**

Other ecotoxicological advice:

The product has been assessed on the basis of the components' available data. To some extent data gaps exist for individual components.

# 13. Disposal Considerations

#### Waste treatment methods

Must be disposed of or incinerated in accordance with local regulations.

A waste code in accordance with the European waste catalog (EWC) cannot be specified, due to dependence on the usage.

Date / Revised: 22.11.2019 Version: 1.0

Product: Ultrafuse® ABS nat.-acrylonitrile butadiene styrene filament

(ID no. 11120801/SDS\_GEN\_00/EN)

Date of print 19.03.2021

The waste code in accordance with the European waste catalog (EWC) must be specified in cooperation with disposal agency/manufacturer/authorities.

Contaminated packaging:

Packs that cannot be cleaned should be disposed of in the same manner as the contents. Uncontaminated packaging can be re-used.

# 14. Transport Information

#### **Land transport**

**ADR** 

Not classified as a dangerous good under transport regulations

UN number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

**RID** 

Not classified as a dangerous good under transport regulations

UN number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

# **Inland waterway transport**

ADN

Not classified as a dangerous good under transport regulations

UN number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user:

Transport in inland waterway vessel

Not evaluated

Date / Revised: 22.11.2019 Version: 1.0

Product: Ultrafuse® ABS nat.-acrylonitrile butadiene styrene filament

(ID no. 11120801/SDS\_GEN\_00/EN)

Date of print 19.03.2021

## Sea transport

**IMDG** 

Not classified as a dangerous good under transport regulations

UN number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

#### Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

UN number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

# Transport in bulk according to Annex II of MARPOL and the IBC Code

Regulation:
Shipment approved:
Pollution name:
Pollution category:
Ship Type:
Not evaluated
Not evaluated
Not evaluated
Not evaluated
Not evaluated

# 15. Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Not applicable

#### 16. Other Information

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a

Date / Revised: 22.11.2019 Version: 1.0

Product: Ultrafuse® ABS nat.-acrylonitrile butadiene styrene filament

(ID no. 11120801/SDS\_GEN\_00/EN)

Date of print 19.03.2021

Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.