



MOUNTING SUGGESTIONS

Honda VT1100 ACE1995-2001 Solo and Passenger Seat

Hardware:

Solo seat:
Stock side bolts

1/4"-20x3/4" screws x2

Passenger seat:
stock rear bolt or
nut
White nylon washer

Tools needed: 10mm and 12mm wrench
Phillips screwdriver

Removal of stock seat:

1. Remove the bolt or nut from the back of the passenger seat with a 10mm wrench and set aside. This bolt is used to mount your Mustang seat.
2. Remove the stock side mounting bolts from either side of the seat with a 12mm wrench.
3. Slide the seat back and lift to remove from the motorcycle.



Installation of Mustang seat:

1. Ensure the passenger seat is firmly secured to the solo.
2. Engage the front bracket into the frame receptacle. This is located lower than the fuel tank flange.
3. Position a nylon washer between the rear bracket and the fender and install the stock rear bolt or nut loosely.
4. Secure the seat with the two stock side bolts.
5. Tighten the rear bolt or nut.

Enjoy the comfort and custom look of your new Mustang seat!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 8:30 - 5:00 Eastern or send an e-mail to tech@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers: 75010, 75011, 75013, 75014, 75015, 75016



Products made by Mustang Motorcycle Products, LLC are warranted for one year against defects in material and workmanship. Mustang must first be notified of any apparent defect. A return authorization will be issued. Carefully pack the product and return prepaid. Upon receipt, Mustang will make a fair, prompt decision regarding repair or replacement.

Incidental and consequential damages arising from or in connection with the installation or use of a Mustang product are not covered by this warranty. An original purchase receipt must be provided to obtain a warranty repair or replacement.