



MOUNTING SUGGESTIONS

Harley-Davidson® FLHT and FLTR 1997-2007 Cyclone Solo Seat and Frame Mounting Plate

Hardware:	#B30125 steel nose bracket x1
(Included)	5/8" thick rubber bumpers x2
	1/4"-20x3/4" long screw and washer x1
	1/4"-20x1/2" long screws x2
	1/4"-20x1-1/2" long screws with washers x2
	1/4"-20 chrome acorn nuts with chrome washers x2

Install Cyclone solo seat onto frame mounting plate:

1. Attach nose bracket #B30125 to bottom of Cyclone seat using the two 1/4"-20x1/2" long screws.
2. The 1/4"-20x3/4" long screw with a flat washer must be inserted through the frame mounting plate from the bottom, and then into the threaded hole in the nose bracket.
3. The two 1/4"-20x1-1/2" long screws and washer must be inserted through the frame mounting plate from the bottom, then through the two 5/8" thick rubber bumpers, and finally into the two threaded inserts toward the rear of the solo seat.

4. Tighten all three screws.

Install frame mounting plate onto bike frame.

1. Slide the nose tab on bottom of frame mounting plate into the hole in the bike frame just behind the gas tank.
2. Align the two rear mounting holes with the two 1/4"-20 threaded studs in the front of the rear fender.
3. Attach frame mounting plate to bike using the two 1/4"-20 chrome acorn nuts with chrome washers.



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 8:30 - 5:00 Eastern or send an e-mail to tech@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers: 76615, 76616, 76617, 76618, 76621

Frame mounting plate: 76622



Products made by Mustang Motorcycle Products, LLC are warranted for one year against defects in material and workmanship. Mustang must first be notified of any apparent defect. A return authorization will be issued. Carefully pack the product and return prepaid. Upon receipt, Mustang will make a fair, prompt decision regarding repair or replacement.

Incidental and consequential damages arising from or in connection with the installation or use of a Mustang product are not covered by this warranty. An original purchase receipt must be provided to obtain a warranty repair or replacement.