

Date Issued: 06/22/2021

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT DESCRIPTION: NUGENESIS ACTIVATOR LIQUID

MANUFACTURER

24 HR. EMERGENCY TELEPHONE NUMBER

CANUTEC 1 888-226-8832

NUGENESIS NAILS INC.

41 BUTTERMILL AVE. CONCORD ONTARIO L4K

3X1 Phone: 905-761-8881

Emergency Contact: CANUTEC Emergency Phones:

1-888-226-8832

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Target Organ Toxicity (Single exposure), Category 3 Serious Eye Damage/Eye Irritation, Category 2A Acute Toxicity (Oral), Category 4

Physical:

Flammable Liquids, Category 2

GHS LABEL

Note: If this product is a consumer product it is labeled in accordance with the Consumer Product Safety Commission regulations and not OSHA regulations. The requirements for the labeling of consumer products take precedence over OSHA labeling so the actual product label will not contain the OSHA label elements shown below on this SDS.





Exclamation mark

Flame

SIGNAL WORD: DANGER HAZARD STATEMENTS

H225: Highly flammable liquid and vapour.

H302: Harmful if swallowed.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

PRECAUTIONARY STATEMENTS

Prevention:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233: Keep container tightly closed.

P240: Ground and bond container and receiving equipment.

P242: Use non-sparking tools.

P243: Take action to prevent static discharges.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P264: Wash skin and hands thoroughly after handling.



Date Issued: 06/22/2021

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P301+312: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P330: Rinse mouth.

P337+P313: If eye irritation persists: Get medical advice/attention.

P370+P378: In case of fire: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment for extinction.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P403+P235: Store in a well-ventilated place. Keep cool.

P405: Store locked up.

Disposal:

P501: Dispose of in a manner consistent with federal, state, and local regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Ethyl Acetate	85 - 100	141-78-6
Pentanone	< 1	107-87-9
Methyl-Isobutyl Ketone (MIBK)	< 1	108-10-1
Dimethyltolylamine	< 1	99-97-8

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Get immediate medical attention.

SKIN: Wash with soap and water. Get medical attention if irritation develops or persists.

INGESTION: If swallowed, seek medical advice immediately and show this container or label.

INHALATION: Remove to fresh air. Get medical attention if breathing is difficult.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE EFFECTS: Vapors may be irritating to eyes, throat and mucous membranes; ingestion may cause headache, drowsiness and possible unconsciousness.

5. FIRE FIGHTING MEASURES

GENERAL HAZARD: Highly flammable. Irritant.

EXTINGUISHING MEDIA: Use dry chemical, foam or carbon dioxide.

EXPLOSION HAZARDS: Vapors can travel to a source of ignition and flash back.

FIRE FIGHTING PROCEDURES: Avoid using large quantities of water.



Date Issued: 06/22/2021

FIRE FIGHTING EQUIPMENT: As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide or carbon dioxide.

6. ACCIDENTAL RELEASE MEASURES

LARGE SPILL: Dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material on adsorbent, such as sawdust or vermiculite, and sweep into closed containers for disposal. After all visible traces, including ignitible vapors, have been removed thoroughly wet vacuum the area. Do not flush to sewer. If area of spill is porous, remove as much contaminated earth and gravel, etc. as necessary and place in closed containers for disposal.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: This product is readily biodegradable. Do not release into surface waters.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Avoid breathing of vapors. Use only in well ventilated areas. When handling, do not eat, drink or smoke.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HA	ZARDOUS COMPON	ENTS (29	9 CFR1910.1200)		
	EXPOSURE LIMITS				
Chemical Name	Туре		ppm	mg/m³	
Ethyl Acetate	OSHA PEL	TWA	400	1400	
	ACGIH TLV	TWA	400	1440	
Methyl-Isobutyl Ketone (MIBK)	OSHA PEL	TWA	100	410	
	ACGIH TLV	TWA	20	-	
		STEL	75		
Dimethyltolylamine	OSHA PEL	TWA	0.50 ppm	Not Established	
		STEL	Not Established	Not Established	
	ACCIH TI V	TWA	Not Established	Not Established	
	ACGIH TLV ST	STEL	Not Established	Not Established	

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Avoid contact with eyes.

SKIN: Wear suitable gloves.

RESPIRATORY: Use only in a well-ventilated area. In case of insufficient ventilation, wear suitable respiratory equipment.

Recommended: Full-face NIOSH-approved respirator with organic vapor cartridge.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid **ODOR:** Strong fruity odor.



Date Issued: 06/22/2021

ODOR THRESHOLD: Not Established **APPEARANCE:** Clear, Colorless liquid

COLOR: Clear to pale yellow

pH: Not Established

PERCENT VOLATILE: No data available

FLASH POINT AND METHOD: 1.11°C (30°F) TCC

FLAMMABLE LIMITS: 2 to 11.4

AUTOIGNITION TEMPERATURE: 427°C (800.6°F) **VAPOR PRESSURE:** 73 mmHg at 20°C (68°F)

VAPOR DENSITY: No data available

BOILING POINT: 77°C (170°F) to 78°C (172°F)

FREEZING POINT: No data available MELTING POINT: Not Established

THERMAL DECOMPOSITION: Not Established

SOLUBILITY IN WATER: Slightly soluble.

EVAPORATION RATE: 4.5 (n-Butyl Acetate=1)

SPECIFIC GRAVITY: 0.9 (water=1) VISCOSITY #1: < 5 Centipoise

(VOC): 9 g/L

10. STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: No

CONDITIONS TO AVOID: Heat, sparks and flame.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, dioxide. **INCOMPATIBLE MATERIALS:** Strong oxidizing agents, acids and bases.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Chemical Name	ORAL LD ₅₀	DERMAL LD ₅₀	INHALATION LC ₅₀
Ethyl Acetate	5620 mg/kg (rat)	180000 mg/kg (rabbit)	45000 mg/m3 per 2 hrs (mouse)
Pentanone	1600 mg/kg	> 20 mg/kg (guinea pig)	
Methyl-Isobutyl Ketone (MIBK)	2080 mg/kg	> 10 mg/kg	
Dimethyltolylamine	1650 mg/kg (rat)	> 2000 mg/kg (rat)	498 mL/m3

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: This product is readily biodegradable. Do not release into surface waters.

AQUATIC TOXICITY (ACUTE)

96-HOUR LC₅₀: > 220 mg/L (Golden orfe)



Date Issued: 06/22/2021

48-HOUR EC₅₀: > 500 mg/L (Daphnia) **96-HOUR EC**₅₀: > 360 mg/L (green algae)

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of in accordance with all local, state, and federal regulations.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: UN1173, ETHYL ACETATE, 3, II (LTD QTY, IP VOL LESS THAN OR EQUAL TO 1.0 L), Ltd. Qty. AIR (ICAO/IATA)

SHIPPING NAME: ID8000, CONSUMER COMMODITY, 9 (IPVOL LESS THAN OR EQUAL TO 0.5 L); or UN1173, ETHYL ACETATE, 3, II (LTD QTY, IP VOL LESS THAN OR EQUAL TO 0.5 L)*

VESSEL (IMO/IMDG)

SHIPPING NAME: UN1173, ETHYL ACETATE, 3, II (LTD QTY, IP VOL LESS THAN OR EQUAL TO 1.0 L)*

COMMENTS: * This product may be shipped as EXCEPTED QUANTITIES OF CLASS 3, UN1173 (IP VOL LESS THAN OR EQUAL TO 0.03 L, OP VOL LESS THAN OR EQUAL TO 0.5 L)

The transport information provided in this section only applies to the material formulation/itself, and is not specific to any package/configuration. This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. It is the responsibility of the transporting organizations to follow all applicable laws, regulations, and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

CERCLA (COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT)

Chemical Name	Wt.%	CERCLA RQ
Ethyl Acetate	85 - 100	5,000 lbs.
Methyl-Isobutyl Ketone (MIBK)	< 1	5,000

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
Ethyl Acetate	141-78-6
Pentanone	107-87-9
Methyl-Isobutyl Ketone (MIBK)	108-10-1
Dimethyltolylamine	99-97-8

TSCA STATUS: All ingredients in this mixture are in compliance with TSCA.

CALIFORNIA PROPOSITION 65: A WARNING: This product can expose you to chemicals including Methyl Isobutyl Ketone (MIBK), which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



Date Issued: 06/22/2021

Chemical Name	Wt.%	Listed
Methyl-Isobutyl Ketone (MIBK)	< 1	Cancer Developmental Toxicity
Dimethyltolylamine	< 1	Cancer


GENERAL COMMENTS: Massachusetts Right to Know Components: Ethyl acetate (CAS 141078-6), Pennsylvania Right to Know Components: Ethyl acetate (CAS 141078-6), New Jersey Right to Know Components: Ethyl acetate (CAS 141078-6)

16. OTHER INFORMATION

REVISION SUMMARY: This SDS replaces the 05/15/2019 SDS.

Date Revised: 12/05/2019

HMIS RATING HEALTH 1 FLAMMABILITY 3 PHYSICAL HAZARD 0 PERSONAL PROTECTION



MANUFACTURER DISCLAIMER: To the best of our knowledge, the information contained herein is accurate. However, NuGenesis Nails Inc. does not assume any liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.