## 16-Present Tacoma

## **RCI Rear Bumper Installation**

- 1. Remove OEM receiver hitch, rear bumper, and wiring harness.
- 2. Remove the plastic covers found directly below the tail lights (as shown in picture). These will interfere with the RCI bumper if left in place.
- 3. Pre-install the bumper wiring harness, license plate lights, and backup sensors (if equipped). Use zip ties to secure the harness to the bumpers center gusset.
- 4. With the help of two people OR preferably using a lift cart or floor jack, lift the bumper into place and loosely secure with at least two bolts per side.
- 5. Adjust bumper height and position relative to body indents on outer wings. You will want approximately ½" clearance between the tail lights to prevent damage with off-road use. Check clearance on both sides of tailgate when opening and closing, as well as below tailgate when in the open position.
- 6. Fully secure bumper, re-using the OEM M14 bolts.
- 7. Re-connect wire harness to truck.
- 8. Bolt the license plate bracket to the pre-drilled holes on the bumper using the supplied #12 self-tapping screws.
- 9. Bolt license plate to the license plate bracket using the supplied ¼" panhead screws and lock-nuts.

## Enjoy the new protection!!!





## Included Hardware

A.	¼-20 x ½" Pan Head Screw	2 ea.
В.	#12 x ¾" Self-Tapping Screw	2 ea.
C.	¼"-20 External Tooth Locknut	2 ea.
D.	Flip-up License Plate Bracket	1 ea.
E.	Backup Light hole covers	2 ea.
F.	M8x 25mm Button Head Bolt	4 ea.
G	5/16" Washers	8 ea.
н.	M8 x 1.25 Nylon Lock-nut	4 ea.





Disclaimer: The products sold by RCI Metalworks are intended for off —road use only, should not be modified, and are for use only on the vehicle(s) specifically stated. RCI Metalworks makes no warranties express or implied, including of fitness for a particular purpose or merchantability. RCI Metalworks will not be liable for any damages arising out of the use or misuse of its products. It is the customers' responsibility to ensure the products are safely and properly attached to the vehicle, and all products should be installed by trained professionals. We strive to maintain extremely high quality standards; however, all RCI Metalworks products are individually handcrafted, may vary slightly, and may contain minor imperfections. Due to the nature of raw aluminum, the material may have minor scratches and other blemishes caused by the manufacturing process, especially on the back side of product. RCI Metalworks is constantly seeking to improve its products and reserves the right to make changes to any product.