

## SIZES & SPECIFICATIONS



### 16" Size Specs

TIRE SIZE	LOAD / SPEED	LOAD ID	SIDEWALL	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS.)	TREAD DEPTH (1/32")	INFLATED OVERALL DIAMETER (IN.)	INFLATED OVERALL WIDTH (IN.)	MAX LOAD SINGLE / DUAL (LBS.)	MAX PRESSURE SINGLE / DUAL (PSI)	UTQG	REVS PER MILE
LT235/85R16	120/116R	E	BSW	6.0-6.5-7.5	44	16	31.7	9.3	3042/2778	80/80	-	655
LT245/75R16	120/116S	E	BSW	6.5-7.0-8.0	44	16.1	30.5	9.8	3042/2778	80/80	-	682
LT245/75R16	120/116S	E	OWL	6.5-7.0-8.0	44	16.1	30.7	9.8	3042/2778	80/80	-	676
LT265/75R16	123/120R	E	BSW	7.0-7.5-9.0	50	16.3	31.7	10.5	3415/3085	80/80	-	656
LT265/75R16	123/120R	E	OWL	7.0-7.5-9.0	48	16.3	31.9	10.5	3415/3085	80/80	-	651
LT285/75R16	126/123R	E	OWL	7.5-8.0-9.5	56	16.5	33.1	11.3	3750/3415	80/80	-	628
LT285/75R16	126/123R	E	BSW	7.5-8.0-9.5	59	16.5	32.8	11.3	3750/3415	80/80	-	633
LT305/70R16	124/121R	E	BSW	8.0-9.0-10.0	63	16.8	32.8	12.2	3525/3195	65/65	-	633
LT315/75R16	127/124R	E	BSW	8.0-8.5-10.5	65	16.9	34.6	12.3	3860/3525	65/65	-	601

### 17" Size Specs

TIRE SIZE	LOAD / SPEED	LOAD ID	SIDEWALL	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS.)	TREAD DEPTH (1/32")	INFLATED OVERALL DIAMETER (IN.)	INFLATED OVERALL WIDTH (IN.)	MAX LOAD SINGLE / DUAL (LBS.)	MAX PRESSURE SINGLE / DUAL (PSI)	UTQG	REVS PER MILE
LT255/75R17	111/108S	C	BSW	6.5-7.0-8.5	48	16.3	32	10	2405/2205	50/50	-	648
LT255/80R17	121/118R	E	BSW	6.5-7.0-8.5	50	16.3	33.1	10	3195/2910	80/80	-	628
LT265/70R17	121/118S	E	BSW	7.0-8.0-9.0	48	16.3	31.7	10.7	3195/2910	80/80	-	656

**17" Size Specs**

TIRE SIZE	LOAD / SPEED	LOAD ID	SIDEWALL	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS.)	TREAD DEPTH (1/32")	INFLATED OVERALL DIAMETER (IN.)	INFLATED OVERALL WIDTH (IN.)	MAX LOAD SINGLE / DUAL (LBS.)	MAX PRESSURE SINGLE / DUAL (PSI)	UTQG	REVS PER MILE
LT265/70R17	121/118S	E	OWL	7.0-8.0-9.0	48	16.3	31.7	10.7	3195/2910	80/80	-	656
LT265/70R17	112/109T	C	BSW	7.0-8.0-9.0	50	16.3	31.7	10.7	2470/2270	50/50	-	656
LT285/70R17	116/113Q	C	BSW	7.5-8.5-9.5	55	16.5	32.8	11.5	2755/2535	50/50	-	634
LT285/70R17	121/118S	E	OWL	7.5-8.5-9.5	53	16.5	33	11.5	3195/2910	80/80	-	630
LT285/70R17	121/118S	E	BSW	7.5-8.5-9.5	55	16.5	32.8	11.5	3195/2910	80/80	-	634
LT285/75R17	117/114Q	C	BSW	7.5-8.0-9.5	59	16.5	33.9	11.3	2835/2600	50/50	-	614
LT285/75R17	121/118S	E	BSW	7.5-8.0-9.5	60	16.5	33.9	11.3	3195/2910	80/80	-	614
33X12.50R17LT	124S	F	BSW	8.5-10.0-11.0	60	16.9	32.5	12.5	3525/-	80/-	-	639
35X12.50R17LT	121R	E	BSW	8.0-10.0-10.5	65	16.9	34.5	12.5	3195/-	65/-	-	602
35X12.50R17LT	111Q	C	BSW	8.0-10.0-10.5	59	16.9	34.5	12.5	2405/-	35/-	-	602
37X12.50R17LT	128S	E	BSW	8.0-10.0-10.5	73	16.9	36.5	12.5	3970/-	65/-	-	569
LT315/70R17	121/118S	D	BSW	8.0-9.5-10.5	67	16.9	34.4	12.7	3195/2910	50/50	-	604
37X13.50R17LT	128S	E	BSW	9.0-11.0-11.5	79	16.9	36.5	13.6	3970/-	65/-	-	569

**18" Size Specs**

TIRE SIZE	LOAD / SPEED	LOAD ID	SIDEWALL	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS.)	TREAD DEPTH (1/32")	INFLATED OVERALL DIAMETER (IN.)	INFLATED OVERALL WIDTH (IN.)	MAX LOAD SINGLE / DUAL (LBS.)	MAX PRESSURE SINGLE / DUAL (PSI)	UTQG	REVS PER MILE
LT265/70R18	124/121Q	E	BSW	7.0-8.0-9.0	51	16.3	32.6	10.7	3525/3195	80/80	-	636
LT275/65R18	113/110T	C	OWL	8.0-9.5	51	16.4	32.3	11	2535/2335	50/50	-	643
LT275/65R18	113/110T	C	BSW	8.0-9.5	51	16.4	32.1	11	2535/2335	50/50	-	647
LT275/65R18	123/120S	E	BSW	8.0-9.5	52	16.4	32.1	11	3415/3085	80/80	-	647
LT275/65R18	123/120S	E	OWL	8.0-9.5	51	16.4	32.3	11	3415/3085	80/80	-	643
LT275/70R18	125/122S	E	BSW	7.0-8.0-9.0	53	16.4	33.2	11	3640/3305	80/80	-	626
LT275/70R18	125/122S	E	OWL	7.0-8.0-9.0	52	16.4	33.2	11	3640/3305	80/80	-	626
LT285/65R18	125/122S	E	BSW	8.5-10.0	55	16.5	32.6	11.5	3640/3305	80/80	-	638
LT285/70R18	127/124S	E	BSW	7.5-8.5-9.5	57	16.5	33.7	11.5	3860/3525	80/80	-	616
LT285/75R18	129/126S	E	BSW	7.5-8.0-9.5	65	16.5	34.8	11.3	4080/3750	80/80	-	596
LT295/70R18	129/126S	E	BSW	7.5-8.5-10.0	63	16.6	34.3	11.8	4080/3750	80/80	-	606
33X12.50R18LT	122Q	F	BSW	8.5-10.0-11.0	65	16.9	32.5	12.5	3305/-	80/-	-	639
35X12.50R18LT	128Q	F	BSW	8.5-10.0-11.0	75	16.9	34.5	12.5	3970/-	80/-	-	602
35X12.50R18LT	118R	D	BSW	8.5-10.0-11.0	66	16.9	34.5	12.5	2910/-	50/-	-	602
LT305/65R18	128/125Q	F	BSW	9.0-11.0	65	16.8	33.6	12.2	3970/3640	80/80	-	619

## SIZES AND SPECIFICATIONS LEGEND

### Speed Rating

M = 81 mph  
N = 87 mph  
P = 93 mph  
Q = 99 mph  
R = 106 mph  
S = 112 mph

T = 118 mph  
H = 130 mph  
V = 149 mph  
W = 168 mph  
Y = 186 mph  
(Y) = 195 mph

### Load ID

SL = Standard Load  
XL = Extra Load  
RD = Reinforced  
C = 6-ply rating  
D = 8-ply rating  
E = 10-ply rating  
F = 12-ply rating

### Sidewall

BSW = Black Sidewall  
OWL = Outlined White Letters

### Approved Rim Width Range

Bold designates measuring rim width.