

SIZES & SPECIFICATIONS



16" Size Specs

TIRE SIZE	LOAD / SPEED	LOAD ID	SIDEWALL	TREAD DEPTH (1/32")	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS.)	INFLATED OVERALL DIAMETER (IN.)	INFLATED OVERALL WIDTH (IN.)	MAX LOAD SINGLE / DUAL (LBS.)	MAX PRESSURE SINGLE / DUAL (PSI)	UTQG	REVS PER MILE
LT235/85R16	120/116P	E	BSW	18.4	6.0-6.5-7.5	54	32	9.4	3042/2778	80/80	N/A	648
LT245/75R16	120/116P	E	BSW	18.4	6.5-7.0-8.0	52	30.7	9.9	3042/2778	80/80	N/A	674
LT255/85R16 (33X10.00R16)	123/120P	E	BSW	18.9	6.5-7.0-8.0	61	33.5	10.2	3415/3085	80/80	N/A	620
LT265/75R16	123P	E	BSW	18.9	7.0-7.5-8.0	61	31.8	10.8	3415/-	80/-	N/A	651
LT285/75R16 (33X11.50R16)	126P	E	BSW	19.1	7.5-8.0-9.0	67	33	11.6	3750/-	80/-	-	628
LT305/70R16 (33.0X12.00R16)	124P	E	BSW	20	8.0-9.0-9.5	70	33	12.2	3525/-	65/-	N/A	628
LT315/75R16 (35X12.50R16)	127Q	E	BSW	21	8.0-8.5-10.0	81	34.9	12.9	3860/-	65/-	N/A	595
LT385/70R16 (38X14.50R16)	130Q	D	BSW	21	10.0-11.0-12.0	101	37.7	15.6	4190/-	50/-	N/A	550

17" Size Specs

TIRE SIZE	LOAD / SPEED	LOAD ID	SIDEWALL	TREAD DEPTH (1/32")	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS.)	INFLATED OVERALL DIAMETER (IN.)	INFLATED OVERALL WIDTH (IN.)	MAX LOAD SINGLE / DUAL (LBS.)	MAX PRESSURE SINGLE / DUAL (PSI)	UTQG	REVS PER MILE
LT255/75R17	111/108Q	C	BSW	18.3	6.5-7.0-8.5	57	32.3	10	2405/2205	50/50	N/A	644
LT255/80R17	121/118Q	E	BSW	18.3	6.5-7.0-8.5	61	33.3	10	3195/2910	80/80	N/A	624
LT265/70R17	121P	E	BSW	18.9	7.0-8.0-8.5	59	32	10.8	3195/-	80/-	N/A	648
LT285/70R17	121/118P	E	BSW	18.9	7.5-8.5-9.0	64	33	11.5	3195/2910	80/80	N/A	630
LT285/70R17	116/113Q	C	BSW	18.9	7.5-8.5-9.0	65	33	11.5	2755/2535	50/50	N/A	630

17" Size Specs

TIRE SIZE	LOAD / SPEED	LOAD ID	SIDEWALL	TREAD DEPTH (1/32")	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS.)	INFLATED OVERALL DIAMETER (IN.)	INFLATED OVERALL WIDTH (IN.)	MAX LOAD SINGLE / DUAL (LBS.)	MAX PRESSURE SINGLE / DUAL (PSI)	UTQG	REVS PER MILE
LT285/75R17 (34X11.50R17)	121P	E	BSW	19.1	7.5-8.0-9.5	69	34.1	11.6	3195/-	80/-	N/A	608
LT285/75R17	117/114Q	C	BSW	19.1	7.5-8.0-9.5	67	34.1	11.3	2835/2600	50/50	-	609
LT295/70R17 (33X11.50R17)	128P	E	BSW	19.4	7.5-8.5-10.0	68	33.5	11.9	3970/-	80/-	N/A	619
33X12.50R17LT	120Q	E	BSW	21	8.5-10.0-11.0	70	32.8	12.5	3085/-	65/-	N/A	634
35X12.50R17LT	125Q	E	BSW	21	8.5-10.0-11.0	78	34.8	13.2	3640/-	65/-	N/A	596
37X12.50R17LT	124Q	D	BSW	21	8.5-10.0-11.0	84	36.8	12.5	3525/-	50/-	N/A	565
LT315/70R17	121/118Q	E	BSW	20.2	8.0-9.5-11.0	78	34.6	12.7	3195/2910	65/65	N/A	600
LT315/70R17	113/110Q	C	BSW	20.2	8.0-9.5-11.0	76	34.6	12.7	2535/2335	35/35	N/A	600
37X13.50R17LT	131Q	E	BSW	21	8.5-11.0	94	37	14.6	4300/-	65/-	N/A	560
40X13.50R17LT	121Q	C	BSW	21	8.5-11.0	104	39.7	14.4	3195/-	35/-	N/A	522

18" Size Specs

TIRE SIZE	LOAD / SPEED	LOAD ID	SIDEWALL	TREAD DEPTH (1/32")	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS.)	INFLATED OVERALL DIAMETER (IN.)	INFLATED OVERALL WIDTH (IN.)	MAX LOAD SINGLE / DUAL (LBS.)	MAX PRESSURE SINGLE / DUAL (PSI)	UTQG	REVS PER MILE
LT265/70R18	124/121Q	E	BSW	18.9	7.0-8.0-9.0	60	32.9	10.7	3525/3195	80/80	N/A	632
LT275/65R18	123/120P	E	BSW	18.9	7.5-8.0-9.0	63	32.3	11	3415/3085	80/80	N/A	643
LT275/70R18 (33X11.00R18)	125P	E	BSW	19.1	7.0-8.0-8.5	65	33.6	11	3640/-	80/-	N/A	617
LT285/65R18	125/122Q	E	BSW	18.9	8.5-10.0	67	32.8	11.5	3640/3305	80/80	-	633
LT285/70R18 (34X11.50R18)	127/124Q	E	BSW	18.9	7.5-8.5-9.5	70	34.1	11.4	3860/3525	80/80	N/A	609

18" Size Specs

TIRE SIZE	LOAD / SPEED	LOAD ID	SIDEWALL	TREAD DEPTH (1/32")	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS.)	INFLATED OVERALL DIAMETER (IN.)	INFLATED OVERALL WIDTH (IN.)	MAX LOAD SINGLE / DUAL (LBS.)	MAX PRESSURE SINGLE / DUAL (PSI)	UTQG	REVS PER MILE
LT285/75R18 (35X11.5R18)	129P	E	BSW	19.1	7.5-8.0-9.5	72	35.1	11.6	4080/-	80/-	N/A	591
LT295/70R18	129/126P	E	BSW	19.4	7.5-8.5-10.0	72	34.5	11.8	4080/3750	80/80	N/A	602
33X12.50R18LT	118Q	E	BSW	21	8.5-10.0-11.0	74	33	12.7	2910/-	65/-	N/A	630
33X12.50R18LT	122Q	F	BSW	21	8.5-10.0-11.0	74	32.8	12.5	3305/-	80/-	N/A	634
35X12.50R18LT	123Q	E	BSW	21	8.5-10.0-11.0	81	35	13.2	3415/-	65/-	N/A	593
35X12.50R18LT	128Q	F	BSW	21	8.5-10.0-11.0	81	34.8	12.5	3970/-	80/-	N/A	598
LT305/65R18	128/125Q	F	BSW	19.5	8.5-9.0-11.0	71	33.8	12.2	3970/3640	80/80	N/A	614
LT315/70R18 (36X13.00R18)	127/124Q	E	BSW	20.7	8.0-9.5-11.0	81	35.7	13	3860/3525	65/65	N/A	581
37X13.50R18LT	124Q	D	BSW	21	8.5-11.0	90	37	14.2	3525/-	50/-	N/A	560
38X13.50R18LT	126Q	D	BSW	21	8.50-11.0	92	37.7	14.3	3750/-	50/-	N/A	550
38X15.50R18LT	128Q	D	BSW	21	11.0-12.0-13.0	103	37.7	15.9	3970/-	50/-	N/A	550

SIZES AND SPECIFICATIONS LEGEND

Speed Rating

M = 81 mph
 N = 87 mph
 P = 93 mph
 Q = 99 mph
 R = 106 mph
 S = 112 mph
 T = 118 mph
 H = 130 mph
 V = 149 mph
 W = 168 mph
 Y = 186 mph
 (Y) = 195 mph

Load ID

SL = Standard Load
 XL = Extra Load
 RD = Reinforced
 C = 6-ply rating
 D = 8-ply rating
 E = 10-ply rating
 F = 12-ply rating

Sidewall

BSW = Black Sidewall
 OWL = Outlined White Letters

Approved Rim Width Range

Bold designates measuring rim width.